



Cable Strippers

This line of cable strippers includes a double slotted cable stripper for 22/24 AWG wire installation and a coax stripper to perform 2-level and 3-level stripping of RG58/59 coaxial cables. We also offer a combo stripper that cuts and rings Teflon®, smoothly slits fiber, copper and coaxial cables and rings 25-100 pair cable.

- Full line of cable strippers for any job
- Round cable stripper for a variety of flexible round cable
- Coax strippers with two or three levels

To learn more visit: www.flukenetworks.com/strippers

Model	Description
11230002	Cable stripper (round cable)
44210013	Double slotted stripper with cutter, 22/24 gauge
44200013	Double slotted stripper 22/24 gauge
11231257	Coax stripper, 2-level
11231255	Coax stripper, 2 and 3-level
44210015	Double-slotted stripper with cutter, 24/26 gauge



Need-L-Lock™ Crimping Pliers

The Need-L-Lock pliers' patented four-in-one tool combines UR/UY/UG connector crimper with needle-nose pliers so you can carry one less tool on your belt. Aligned crimping jaws come down square ensuring a solid connection. Jaws are grooved to provide a better grip on wires and feature a built-in cutter and wire stripper.

- Needle nose pliers
- UR/UY/UG connector crimper
- Wire stripper hole
- Built-in side cutter
- Rubber coated handles for non-slip grip

To learn more visit: www.flukenetworks.com/pliers

Model	Description
11294000	Need-L-Lock crimping pliers



Probe Pic

This handy, pocket-sized insulation probe is ideal for checking for loose or damaged connections or to spread apart wires for direct access. Its compact size also makes it perfect for using the pic end for tracing or pulling wires from a bunch.

- Trace and pull wires with the pic end
- Check for loose or damaged connections
- Spread apart wires for direct access

To learn more visit: www.flukenetworks.com/pic

Model	Description
44600000	Probe pic, 105 degree



Can Wrench

This can wrench allows universal access to telephone boxes and pedestals. Open telephone box fasteners and tightens nuts on binding post terminals.

- Two hex head sockets (7/16 inch and 3/8 inch)
- Color-coded socket ends for quick size identification
- Wrench body constructed of tough, impact resistant and abrasion resistant material
- Socket ends guaranteed not to split or break up to a maximum torque of 45 pounds
- Two models available with wire stripper in handle (22 or 24 gauge)

To learn more visit: www.flukenetworks.com/wrench

Model	Description
44007000	Can wrench, hex head
44507003	Can wrench with stripper, 22 gauge
44507004	Can wrench with stripper, 24 gauge
10660001	Security key insert