



TS-h1090FU-7302P-128G

CPU AMD EPYC™ 7302P 16-core/32-thread processor, up to 3.3 GHz

CPU Architecture 64-bit x86

Encryption Engine Yes (AES-NI)

System Memory 128 GB RDIMM DDR4 ECC (8 x 16 GB)

Maximum Memory 1 TB+ (12 x 128 GB)

Memory Slot 12 x RDIMM DDR4

Flash Memory 5GB (Dual boot OS protection)

Drive Bay 10 x 2.5-inch U.2 PCIe NVMe / SATA 6Gbps

Drive Compatibility 2.5-inch U.2 NVMe Gen 4 x4 solid state drives
2.5-inch SATA solid state drives

Hot-swappable Yes

SSD Cache Acceleration Support Yes

SR-IOV Yes

2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (2.5G/1G/100M/10M)

25 Gigabit Ethernet Port 2 x 25GbE SFP28 SmartNIC port

Wake on LAN (WOL) Yes

Jumbo Frame Yes

PCIe Slot 2
Slot 1: PCIe Gen4 x16
Slot 2: PCIe Gen4 x16

USB 3.2 Gen 1 port 3

Form Factor Rackmount

LED Indicators Disk, Status, LAN, storage expansion port status

| | |
|---|--|
| Buttons | Power, Reset |
| Dimensions (HxWxD) | 44 × 430 × 580 mm |
| Weight (Net) | 10.36 kg |
| Weight (Gross) | 13.41 kg |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 550W PSU (x2), AC 100-240 V |
| Power Consumption: Operating Mode, Typical | 157.97 W |
| Fan | 5 x 60mm, 12VDC |
| System Warning | Buzzer |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 10,000 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.