



## TS-h973AX-32G

CPU	AMD Ryzen™ Embedded V1500B 4-core/8-thread 2.2 GHz processor
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
System Memory	32 GB SODIMM DDR4 (2 x 16 GB)
Maximum Memory	64 GB (2 x 32 GB)
Memory Slot	2 x SODIMM DDR4 Support optional ECC memory
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	5 x 3.5-inch + 4 x 2.5-inch
Drive Compatibility	<p>3.5-inch bays:</p> <ul style="list-style-type: none"> <li>3.5-inch SATA hard disk drives</li> <li>2.5-inch SATA hard disk drives</li> <li>2.5-inch SATA solid state drives</li> </ul> <p>2.5-inch bays:</p> <ul style="list-style-type: none"> <li>2.5-inch SATA hard disk drives</li> <li>2.5-inch SATA solid state drives</li> <li>2.5-inch U.2 NVMe PCIe Gen3 x4 solid state drives (2.5-inch Bay #1 &amp; #2)</li> </ul>
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (2.5G/1G/100M)
5 Gigabit Ethernet Port (5G/2.5G/1G/100M)	Optional via the QNA-UC5G1T USB to 5GbE network adapter
10 Gigabit Ethernet Port	1 x 10GBASE-T (10G/5G/2.5G/1G/100M)
Wake on LAN (WOL)	Yes

Jumbo Frame	Yes
USB 3.2 Gen 2 (10Gbps) Port	1 x Type-C USB 3.2 Gen 2 3 x Type-A USB 3.2 Gen 2
Form Factor	Tower
LED Indicators	HDD 1-5, SSD 1-4, Power/Status, LAN, USB
Buttons	Power, Reset, USB Copy
Dimensions (HxWxD)	182.65 × 224.6 × 224.1 mm
Weight (Net)	3.52 kg
Weight (Gross)	5.12 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	External, 120 W, AC 100 to 240 V
Power Consumption: HDD Sleep Mode	41.2 W
Power Consumption: Operating Mode, Typical	55.41 W
Fan	1 x 140mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	2000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.