

DATA SHEET of the 2G/3G Communicator  
**LX20B-60**



EBS Sp. z o.o.  
 59 Bronislawa Czecha St.  
 04-555 Warsaw, POLAND  
 E-mail: [sales@ebssmart.com](mailto:sales@ebssmart.com)  
 Technical support: [support@ebssmart.com](mailto:support@ebssmart.com)  
 Webpage: [www.ebssmart.com](http://www.ebssmart.com)

Product name		2G/3G Communicator		
Model		LX20B-60		
Power supply parameters	Voltage supply		13,8V <sub>DC</sub> (acceptable: 12-14V <sub>DC</sub> )	
	Power consumption (average / max)		95mA/125mA@13,8V <sub>DC</sub>	
Modem	Model		Cinterion EHS6	
	Manufacturer		Gemalto M2M GmbH St.-Martin-Str. 60 81541 München Germany	
	Frequencies range	Uplink MS > BTS	GSM850	824 – 849 MHz
			EGSM900	880 – 915 MHz
			GSM1800	1710 – 1785 MHz
			GSM1900	1850 – 1910 MHz
			UMTS800	830 – 840 MHz
			UMTS850	824 – 849 MHz
			UMTS900	880 – 915 MHz
		Downlink BTS > MS	UMTS1900	1850 – 1910 MHz
			UMTS2100	1920 – 1980 MHz
			GSM850	869 – 894 MHz
			EGSM900	925 – 960 MHz
			GSM1800	1805 – 1880 MHz
			GSM1900	1930 – 1990 MHz
			UMTS800	875 – 885 MHz
	RF output power @ ARP with 50Ω load	UMTS850	869 – 894 MHz	
		UMTS900	935 – 960 MHz	
		UMTS1900	1930 – 1990 MHz	
		UMTS2100	2110 – 2170 MHz	
		GSM850	33 dBm ±2dB	
		EGSM900	33 dBm ±2dB	
		GSM1800	30 dBm ±2dB	
GSM1900		30 dBm ±2dB		
UMTS800		24 dBm +1/-3dB		
Receiver input sensitivity @ARP (min / typ)	UMTS850	24 dBm +1/-3dB		
	UMTS900	24 dBm +1/-3dB		
	UMTS1900	24 dBm +1/-3dB		
	UMTS2100	24 dBm +1/-3dB		
	GSM850	-102 dBm / -109 dBm		
	EGSM900	-102 dBm / -109 dBm		
	GSM1800	-102 dBm / -108 dBm		
	GSM1900	-102 dBm / -108 dBm		
	UMTS800	-104.7 dBm / -110 dBm		
UMTS850	-104.7 dBm / -110 dBm			
UMTS900	-103.7 dBm / -110 dBm			
UMTS1900	-104.7 dBm / -109 dBm			
UMTS2100	-106.7 dBm / -110 dBm			

Transmission channels *transparent, PSTN dialer required in a CP	GPRS, EDGE, HSPA+, SMS, PSTN*
Simulated PSTN line	YES
Protocols supported on the phone input	SIA, ContactID
Inputs	5 (NO/NC/EOL-NO/EOL-NC/DEOL-NO/DEOL-NC)
Outputs	2 (OC, max. load 100mA)
Output functions (ways of control)	- loss of UMTS or GSM signal - UMTS or GSM jamming - full control via server or through SMS - in reaction on inputs
Serial interface	RS232 / RS485 (lines: RxD, TxD, RTS, CTS) transmission speed up to 115200bps
Quantity of system events stored in history	5000
Events buffer (GSM dialer function):	1000 events capacity
GPRS/SMS transmission security	AES encryption
Status LEDs (functions)	4 LEDs (GSM signal level, device state, DTMF communication)
Configuration	Remote: GPRS, EDGE, HSPA+, SMS, CSD Local: PC through RS232 (required cable: LX-PROG or SP-PROG)
Remote firmware update	YES
Temperature range of working	-10°C ... +55°C
Humidity range of working	5% ... 93% (without condensation)
Dimension	PCB: 102 x 73 x 20mm