252026-10KT-P



Angle Adapter, miniature, (5/16") tapped hole

Product Classification

Product Type Adapter

Ordering Note CommScope® standard product in Europe, the Middle East, and Africa | CommScope®

standard product in Mexico, Central America, and South America | CommScope® standard

product in the United States and Canada

General Specifications

Adapter Type Angle adapter

Dimensions

Inside Width 16.002 mm | 0.63 in

Outside Width 25.4 mm | 1 in

Inside Length 12.7 mm | 0.5 in

Outside Length 29.972 mm | 1.18 in

Material Thickness 14.224 mm | 0.56 in

Material Specifications

Material Type Stainless steel 304

Mechanical Specifications

Installation Torque, maximum13 ft lb | 17.626 N-mInstallation Torque, minimum11 ft lb | 14.914 N-mMaximum LoadingTriple stack, 1/2 in cable

Packaging and Weights

Height, packed 11.3 cm | 4.449 in

COMMSC PE®

252026-10KT-P

Width, packed10 cm | 3.937 inLength, packed6 cm | 2.362 in

Packaging quantity 10

Weight, gross 0.85 kg | 1.874 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system
REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



