

**55992B**
**20000mAh Power Bank with Built-in Cable**

**Specifications**

- \*USB-C Cable Input: 5V= 3A/9V= 3A/12V= 3A/15V= 3A/20V= 4A 80W Max
- \*USB-C Input: 5V= 3A/9V= 3A/12V= 3A/15V= 3A/20V= 2.25A 45W Max
- \*USB-C Cable Output: 10V= 2.25A/5V= 3A/9V= 3A/12V= 3A/15V= 3A/20V= 5A 100W Max
- \*USB-C Output: 10V= 2.25A/5V= 3A/9V= 3A/12V= 3A/15V= 3A/20V= 2.25A 45W Max
- \*USB-A Output : 10V= 2.25A/5V= 3A/9V= 2A/12V= 1.5A
- \*Multi-port Output
- (USB-C Cable+USB-C): 145W Max
- \*Total Output: 5V= 7A/9V= 6A/12V= 6A/15V= 6A/20V= 7.25A
- \*Total Cell Capacity: 20000mAh
- \*Battery Capacity: 5000mAh (Four Cells in Series)
- \*Rated Energy: 72Wh 14.4V
- \*Rated Capacity: 11000mAh (TYP 5V 7A)
- \*Battery Type: Lithium-ion Battery
- \*Battery Charging Limited Voltage: 4.2V=
- \*Output Capacity: 11000mAh (5V/7A)
- 6500mAh (9V/6A)
- 5900mAh (10V/4.5A)
- 4600mAh (12V/6A) Max
- 3800mAh (15V/6A) Max
- 2800mAh (20V/7.25A) Max
- \*Charging Time: About 1.5 hours (with ≥65W Charger + Built-in USB-C Cable)
- \*Storage Temperature: 0°C-40°C (32°F -104°F )
- \*Operating Temperature: 5°C-35°C (41°F -95°F )
- \*Dimensions: L139×W80×H27 (mm)/L5.5×W3.1×H1.1 (inch)
- \*Package Contents: 1×Power Bank, 1×Charging Cable, 1×User Manual

**Selling points**

**MORE FOR YOU**