



REVISION HISTORY		
REV.	DESCRIPTION	DATE
C	REVISE PER EC3718	2017-03-01
D	REVISED PER EP0002	2019-05-22
E	REVISED PER EP0002	2019-08-12

SPECIFICATIONS

- CERTIFICATIONS: **CE**; **UL**; ECE R10; SAE (SEE CHART); IP-66D/IP-67D for a Category 2, Versatile enclosure
 Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- FLASH MODE: PULSE8 : 80 ± 5 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12-80 VDC
- VOLTAGE (EXTREME): 9-94 VDC
- CURRENT (PEAK): 0.12A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 1.5W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- CONNECTION: 2-16 AWG LEAD WIRES
- MOUNTING: 1/2" PIPE CONDUIT
- BASE MATERIAL: GLASS FILLED NYLON
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 0.72 LBS (0.32 Kg)

FGS. PRODUCT CHART		
FGS. NO.	COLOR	J845 (JUN 2013)
6267A	AMBER	CLASS 3
6267B	BLUE	-
6267C	CLEAR	CLASS 3
6267G	GREEN	-
6267R	RED	CLASS 3

NOTES:
 1. ROHS COMPLIANT
 2. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION
 THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2013 ELECTRONIC CONTROLS COMPANY

SCALE 1:2.25		APPROVALS	DATE
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: A		DRAWN BY ABD	2019-08-09
		CHECKED ABB	2019-08-12
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		MECH. ENG. NMT	2019-08-12
		ELEC. ENG. SPO	2019-08-09
MILLIMETERS DECIMALS XX. ± 1.0mm XX.X ± 0.5mm	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	ANGLES ± 0.5°	
	FRACTIONS ± 1/64	TEST ENG. JRT	2019-08-12
		SALES. ARS	2019-08-09
THIRD ANGLE PROJECTION			

ECCO[®] www.eccolink.com
 Americas (800) 635-5900 | Europe +44 (0)113 237 5340 | Asia Pacific +61 (0)3 63322444

LED BEACON, 360°, 1/2" PIPE, 12-80VDC

CUSTOMER PART NO. SEE CHART		PRODUCT SERIES: 6200
SIZE: A	DWG. NO. 6267X	REV. E
Electronically Controlled Use Latest Copy SHEET 1 OF 1 Project: P12001		Date Created: 2013-02-04