
RACO C BEI HUBBELL 4

MASONRY BOXES & PARTITIONS

Masonry Boxes, 2-1/2 in. Deep - Nongangable with Conduit KO's 1-Gang, 1-31/32 in. Wide





Catalog #: 690

APPLICATIONS

RACO® Masonry boxes are designed to accommodate the mounting of switches or other devices in masonry walls 2-1/2" deep boxes are used in 4" block walls, 3-1/2" deep boxes are used in 6" or 8" block walls

PRODUCT FEATURES

Rugged welded design does not fall apart during construction

Available from one to six gang configurations in both 2-1/2" and 3-1/2" depths Rectangular shape fits square cuts in block Large volume design allows for additional work room inside the box Standard 1/2" and 3/4" concentric knockouts Device ears inside the box prevent mortar from getting in the device holes

Steel voltage partition #971 fits all 2-1/2" or 3-1/2" depths Standard wall plates can be used

N/A

UL LISTED

File E195978

1110 2100010	
GENERAL PRODUCT INFORMATION Wiring System:	Conduit
CONFIGURATION End Knockouts: Drawn or Welded: Gangs: Side Knockout(s): Bottom Knockouts(s):	2 Conc. Welded 1 4 Conc. 2 Conc.
DRAWING DIMENSIONS Dimension A: Dimension B:	2-1/2 in. 1-31/32 in.
PRODUCT MEASUREMENTS Depth: Cubic Inches (cm3): Wt. Ea. (Lbs.): Product Length (in.): Product Width (in.): Product Height (in.):	2-1/2 in. 16.0 (262.2) 0.630 2.50 3.75 1.97
PACKAGING Minimum Pack Qty.: Std. Pkg.: Product UPC-A Labeled: Weight (Lbs. Per/C): Ship Carton Length (in.): Ship Carton Width (in.): Ship Carton Height (in.): Ctn Weight (Lbs.): Pallet Qty: UPC Number: I2of5:	25 25 No 63.00 12.38 6.56 8.75 17.05 2250 050169006900 50050169006900

JOILLINEINIS	
s (cm3):	2-1/2 in. 16.0 (262.2)
.):	0.630
gth (in.):	2.50
th (in.):	3.75
ght (in.):	1.97
ck Qty.:	25
	25
C-A Labeled: Per/C):	No 63.00
Length (in.):	12.38
Width (in.):	6.56
Height (in.):	8.75
Lbs.):	17.05
	2250
er:	050169006900
	50050169006905