




9000 VEHICULAR SLIDE GATE OPERATOR



Powerful & quiet operation

- Steel frame provides strength and quiet operation
- Direct driven limit nuts for precise gate limit control
- Easy to use manual T-handle release
- Built-in power and alarm reset switches, and two 115 VAC convenience outlets
- 5-year limited warranty

RESIDENTIAL • COMMERCIAL • INDUSTRIAL



Entrapment Prevention
reverses gate when obstructed



Built In
power switch and reset switch



Adjustable Partial Open
for different opening distances




Easy To Use
"T-Handle" release

ACCESS CONTROL SOLUTIONS



9000 VEHICULAR SLIDE GATE OPERATOR



9000	1/2 HP	1 HP
CLASS OF OPERATION	I, II, III, IV	I, II, III, IV
MAX GATE LENGTH*	35 ft (10.7 m)	35 ft (10.7 m)
MAX GATE WEIGHT*	1000 lb (454 kg)	1500 lb (680 kg)
MOTOR	1/2 HP Continuous Duty AC Motor	1 HP Continuous Duty AC Motor
INPUT	115 VAC, 60 Hz, 5.4A 208 VAC, 60 Hz, 2.8A** 460 VAC, 60 Hz, 1.4A**	115 VAC, 60 Hz, 9.7A 208 VAC, 60 Hz, 5.0A** 230 VAC, 60 Hz, 4.9A**

* Assumes gate to be in good condition and swinging in a level plane.
 ** These operators use a step-down transformer to achieve 115 VAC operating voltage.

TECHNICAL FEATURES

MECHANICAL

Frame: 3/16 (4.7 mm) steel, corrosion protected
 Cover: 1/4 (6.3 mm) inch polypropylene
 Reduction: belt driven 30:1 gear reduction running in a continuous oil bath
 Speed: Approximately 1 ft (.3 m)/sec (30.5 cm/sec)
 Chain: Unit is shipped with 20 ft (6 m) of #40 roller chain
 Manual Release: "T-Handle" release is easily accessible from front of operator. Operator re-connects automatically when handle is released

GATE TRACKER™

Reporting output provides operator data to a DKS 1833, 1835, 1837 or 1838 access control system (requires 2358 expansion board)

OPTIONS

Heater kits for cold weather operations
 Base Plate for post mounting

ELECTRICAL

Adjustable partial open limit
 Direct driven limit nuts for precise gate control
 Auto-close timer 1-30 seconds
 Selectable loop / reverse input function; stop or reverse
 Anti-tailgating feature helps to control un-authorized traffic
 Standard normally closed stop circuit
 Ports for plug-in open and reverse loop detectors (DKS detectors only)
 Two 115 VAC convenience outlets for accessory transformers

MISCELLANEOUS

Environmental: 10°F to 140°F (-12°C to 62°C)
 Thermostatically controlled heater kit recommended for colder environments
 Shipping weight approximately 145-170 lb (64-77 kg) depending on model and options selected
 Operator requires monitored Type B1 and/or Type B2 entrapment protection devices

Conforms To ANSI/CAN/UL 325:2017 Ed. 7
 Certified To CSA C22.2 #247
 Intertek

DoorKing®, Inc.

Access Control Solutions since 1948



120 S. Glasgow Avenue,
 Inglewood, California 90301 U.S.A.
 Tel: 310-645-0023 FAX: 310-641-1586
 www.doorking.com

© 2019 All Rights Reserved.
 Product specifications may change without notice. Rev. 7/19

MEMBER:



DISTRIBUTED BY:

