



## Single-Phase PDUs



Front View 9LF1-101001



Rear View 9LF1-101001



9LB2-301001

### UL Listed Single-Phase PDUs

Type: B = Basic; L = Local Monitored

Belden Part #	Type	De-Rated Power (kW)	Amps (A)/ Volts (V)	Plug Type	Total Receptacle	Receptacle Type/Qty	Thermal Circuit Breaker	On-Off Switch	Surge Suppression	Monitoring-Local	Mounting (4)	Dimensions L x W x D (in.)
9BF1-061001	B	1.4	15/120	5-15P	6	5-15R/6	Yes	Yes	No	No	Rack - 19"	17 x 1.72 x 3.75
9BF1-061002	B	1.4	15/120	5-15P	6	5-15R/6	Yes	Yes	Yes	No	Rack - 19"	17 x 1.72 x 3.75
9BF1-081001	B	1.4	15/120	5-15P	8	5-15R/8	Yes	Yes	No	No	Vertical	24 x 1.61 x 1.61
9LF1-101001	L	1.4	15/120	5-15P	10	5-15R/10	Yes	Yes	No	Power	Rack - 19"	17 x 1.72 x 4.5
9BF1-141001	B	1.4	15/120	5-15P	14	5-15R/14	Yes	Yes	Yes	No	Vertical	47.5 x 1.61 x 1.61
9BG2-081001	B	1.9	20/120	L5-20P	8	5-20R/8	Yes	Yes	No	No	Vertical	24 x 1.61 x 1.61
9BG1-101001	B	1.9	20/120	L5-20P	10	5-20R/10	Yes	Yes	Yes	No	Rack - 19"	17 x 1.72 x 3.75
9LG1-101001	B	1.9	20/120	L5-20P	10	5-20R/10	Yes	No	No	Power	Rack - 19"	17 x 1.72 x 4.5
9BG1-141001	B	1.9	20/120	L5-20P	14	5-20R/14	Yes	Yes	No	No	Vertical	47.5 x 1.61 x 1.61
9BG2-141001	B	1.9	20/120	L5-20P	14	5-20R/14	Yes	Yes	No	No	Vertical	47.5 x 1.61 x 1.61
9BG1-141002	B	1.9	20/120	L5-20P	14	5-20R/14	Yes	No	Yes	No	Vertical	47.5 x 1.61 x 1.61
9BG2-141002	B	1.9	20/120	L5-20P	14	5-20R/14	Yes	No	Yes	No	Vertical	47.5 x 1.61 x 1.61
9LH2-241001	L	2.8	30/120	L5-30P	24	5-20R/24	Magnetic	Breaker	No	Power	Vertical	66.25 x 2 x 2
9LB2-121001	L	5	30/208	L6-30P	12	C-13/12	Magnetic	Breaker	No	Power	Rack - 19"	17 x 1.72 x 6.5
9LB2-301001	L	5	30/208	L6-30P	30	C-13/24 + C-19/6	Magnetic	Breaker	No	Power	Vertical	66.25 x 2 x 2


- Notes:
- (1) Standard cord length is 10 ft. For other lengths, change dd digit in part # (ex: 9PB2-30dd01 would be 9PB2-300801 = 8 ft). Available in 2, 4, 6, 8, 10, 15, 20 ft.
  - (2) Standard cord exits from chassis face; top of chassis exit available on request.
  - (3) Standard PDU chassis color is black, custom color overlay available on request.



Front View 9PG2-101001



Rear View 9PG2-101001



9OB2-241001

### UL Listed Single-Phase PDUs

Type: P = Remote Power Monitored; O = Outlet Monitored

Belden Part #	Type	De-Rated Power (kW)	Amps (A)/ Volts (V)	Plug Type	Total Receptacle	Receptacle Type/Qty	Thermal Circuit Breaker	On-Off Switch	Monitoring-Local/Remote	Environmental Monitoring	Mounting (4)	Dimensions L x W x D (in.)
9PG2-101001	P	1.9	20/120	5-20P	10	5-20R/10 + 0	Magnetic	No	Power/Aggregate	Yes - 2 Port	Rack - 19"	17 x 1.72 x 6.5
9PB2-301001	P	5	30/208	L6-30P	30	C-13/24 + C-19/6	Magnetic	Breaker	Power/Circuit Breaker	Yes - 2 Port	Vertical	66.25 x 2 x 2.25
9PB2-301002	P	5	30/208	L6-30P	30	C-13L/24 + C-19L/6	Magnetic	Breaker	Power/Circuit Breaker	Yes - 2 Port	Vertical	72 x 2 x 2.25
9PB2-421001	P	5	30/208	L6-30P	42	C-13/36 + C-19/6	Magnetic	Breaker	Power/Circuit Breaker	Yes - 2 Port	Vertical	70 x 2 x 2.25
9OB2-241001	O	5	30/208	L6-30P	24	C-13L/18 + C-19L/6	Magnetic	Breaker	Power/Circuit Breaker + Outlet	Yes - 2 Port	Vertical	72 x 2.25 x 2.25

- Notes:
- (1) Standard cord length is 10 ft. For other lengths, change dd digit in part # (ex: 9PB2-30dd01 would be 9PB2-300801 = 8 ft). Available in 2, 4, 6, 8, 10, 15, 20 ft.
  - (2) Standard cord exits from chassis face; top of chassis exit available on request.
  - (3) C-13L, L refers to receptacles with locking feature.
  - (4) Standard PDU chassis color is black, custom color overlay available on request.
  - (5) These PDUs have no Surge Suppression.