

AE-DC4328-K5 Dashboard Camera

Key Features

 Front 2K HD camera, support 105° horizontally, 123° diagonal rear camera 1080P HD camera;

adjustable up and down, left and right angles 15 $^\circ\,$.

- Display: 3 inch touch screen, Resolution : 854*480.
- Built-in G-Sensor sensor, emergency video starts recording when the vehicle is in collision or severe vibration, and emergency video backup is locked.
- Voice recognition: Support 9 voice commands such as "open screen", "display pre-recording", "display post-recording", "view all", "close screen", "video lock", "I want to take a photo", "open recording", "close recording" etc.
- Communication: Built-in Wi-Fi module.
- Support TF card storage, maximum support 128GB, loop video, seamless connection without missing seconds.
- Support mobile APP connection, real-time viewing of video, video playback and parameter setting.
- Parking monitoring: Support 12 hours/24 hours/48 hours parking monitoring.
- Easy installation, simple operation, plug and record, automatic recording after power on.

Available Model

AE-DC4328-K5









Specifications

Model	AE-DC4328-K5
Camera	
Image sensor	CMOS
Front camera resolution	1440P (2560×1440)
Rear camera resolution	1080P (1920×1080)
Video resolution	When not pulling back: Front: 2160P@30fps, 1440P@30fps, 1080P@30fps When pulling back : Front: 1440P@30fps, 1080P@30fps Rear: 1080P@25fps
Maximum lens angle	Front camera 123° (D), 105° (H), 56° (V)
	Rear camera 125° (D), 110° (H), 62° (V)
Screen	3 inches (854*480)
aperture	F1.55
Video compression	H.265
OSD	Display time, date, etc.
Image format	JPEG
Storage	TF card, 16GB to 128 GB
Communication module	Wi-Fi
Sensor	G-sensor
Interfaces	
Power supply interface	Mini-USB2.0
Audio	MIC Input Suilt-in speaker output
General	
Working temperature	-20 °C to 70 °C (-4 °F to 158 °F)
Working humidity	0% to 95%
Power Supply	5V DC, 2 A
Power consumption	Approx.5W(Rear camera)
Dimension (L x W x H)	89mm × 55mm × 42mm
(without bracket)	(3.50" x 2.16" x 1.65")
Weight (Approx)	110g (0.24 lb)



Dimensions





Distributed by

Γ



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T + 39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2018 | Data subject to change without notice |

20190419