Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX107477 Faceplates and Panels - Patch Box - KeyConnect



For more Information please call

1-800-Belden1



General Description:

KeyConnect Patch Box, 12-port, Black (Empty)

Usa	Usage (Overall)		
	Suitable Applications:	- Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800, 3600, 2400 and 1200.	
	Related Parts:	- Compatible with 10GX, CAT6+ and CAT5E RevConnect and KeyConnect style Modules	

Physical Characteristics (Connectivity)

Max. Capacity: 12 connectors

Access

Front Connection: Flush
Termination Area: Rear

Dimensions

Dimensions:

Height (mm)	Width (mm)	Depth (mm)
69.774	254.000	95.250

Materials

Materials:

Description	Material
Patch Box	Steel

Color

Color: Black

Weight

Weight: 1.145 kg

Included Parts Included Parts:

Packaging
Packaging: Individually packaged in a cardboard box.

Mechanical Characteristics (Connectivity)

Footprint/Type:	KeyConnect
Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C
Operating Temperature Range:	-10°C To +60°C

2 Screws Wood #10x1in; Label, Label Holder

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS):	Yes	

Page 1 of 2 03-13-2017

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX107477 Faceplates and Panels - Patch Box - KeyConnect

	EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
	MII Order #39 (China RoHS):	EUP 50
	Safety Listing:	ACA, Bi-national Standard Listed
Suitability		
	Suitability - Indoor:	Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Product Family

Related Documents:

PX106496-EF RevA.pdf - Installation Guide

Put Ups and Colors:

Ship Weight Color Notes Item Desc Item # Putup

Revision Number: 0 Revision Date: 02-03-2017

© 2017 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHs (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2