

# TP14516, Vinyl Ring Terminal For 16 - 14 AWG

By Burndy Catalog # TP14516

Vinyl Ring Terminal For 16 - 14 AWG.



#### **Features**

- Expanded insulation support accepts standard and large wire diameters providing lower inventory requirements and greater flexibility
- Funnel entry for easy wire insertion
- Manufactured of pure electrolytic copper to provide maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Deep V groove serrations in the inner barrel provides added holding strength and better conductivity

## Application

For Commercial And Light Duty Industrial Control And Power Circuit Applications

## General

Catalog Number	TP14516
Color Code	Blue
Connector Type	Ring Terminal
EU RoHS Indicator	Yes
Feature - Barrel Style	Shrouded
Insulation	Υ
Insulation Type	Vinyl
Material	Copper
Physical Attribute - Number of	1
Holes	
Physical Attribute - Tongue	Ring
Туре	
Plated	Υ
Plating Type	Tin
Sub Brand	COMPRESSION TERMINAL,
	VINYLUG
Trade Name	VINYLUG™
Туре	Ring Tongue
UPC	781810103111
UPC 12 Digit	7818101031111
Insulation Type Material Physical Attribute - Number of Holes Physical Attribute - Tongue Type Plated Plating Type Sub Brand  Trade Name Type UPC	Vinyl Copper 1 Ring Y Tin COMPRESSION TERMINAL, VINYLUG VINYLUG™ Ring Tongue 781810103111

## Dimensions

Cable Insulation Diameter	0.19 in
Maximum	
Dimension - B Length fraction	13/50 in
Dimension - B Length inch	0.26 in
Dimension - Bolt Size fraction	5/16

Dimension - Diameter Max Size	0.19 in
inch	
Dimension - Hole Size fraction	1/3
Dimension - Hole Size inch	0.33 in
Dimension - L Length Overall	31 mm
mm	
Dimension - Length Overall	1.21 in
inch	
Dimension - Pad Width inch	0.53 in
Dimension - Strip Length inch	13/64 in
Dimension - Stud Size inch	5/16 in
Dimension - Z (inch)	0.45 in

## **Electrical Ratings**

Voltage - Maximum 600 V

#### **Conductor Related**

Conductor Range	#16 AWG to #14 AWG
Conductor Size	16 - 14 AWG
Conductor Type	<ul> <li>CU C Solid-Size</li> </ul>
	<ul> <li>CU C Str-Size</li> </ul>

## **Certifications And Compliance**

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL486
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

#### Logistics

Carton Quantity	1200
Minimum Pack Quantity	100
Pallet Quantity	99999

#### **Product Assets**

Catalogs - BURNDY Master Catalog - Section B - Small Compression

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 50093722 Specifications - TP14516



©2025 Hubbell Incorporated. All rights reserved BRDY-TP14516-SPEC-EN  $\mid$  REV 1/2025