

# DC-T4537HRXA

## H.265 5M Bullet Camera / NDAA Compliant



- 5MP (2592x1944) resolution
- Two-way audio
- Built-in heater
- IR LED (Distance : 30m / 98.4ft)
- IDIS Deep-Learning Analytics (IDLA)
- Motorized Vari-focal lens
- Alarm in / out
- Day and night (ICR)
- 3-axis mechanical design for installation
- Easy installation with DirectIP NVR
- micro SD/SDHC/SDXC
- IK10 / IP67 supports
- True wide dynamic range (WDR)
- PoE (IEEE 802.3af Class 3)
- Supports ONVIF

### SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	2.7 - 13.5mm
Aperture	F1.4 - F3.2
Iris Control	DC Iris
Angular Field of View	Wide : 101.2o(H) 72.6o(V) 137.4o(D) Tele : 30.4o(H) 22.8o(V) 38(D)
Min. Illumination	COLOR : 0.15 lux @ F1.4 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 - 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	40m / 131.2 ft (6ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF
Max. Frame Rate	4:3 mode : 30fps : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960, 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, SMTP, FEEN, mDNS, Uppnp, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C - +55°C (-40°F - +131°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% - 90%
Electrical	
Power Source	PoE (IEEE 802.3af Class 3)
Power Consumption	12V=, 1A, 12W PoE, IEEE 802.3af(Class 3), 9.7W
Approval	FCC, CE, KC
Mechanical	
Dimensions	89.3mm X 89.3mm X 277.6mm (3.52" x 3.52" x 10.93")
Weight	1.293kg (2.85lb)



### PRODUCT IMAGE



### DIMENSIONS









(Unit - mm)



### ACCESSORIES (OPTIONAL)

Junction Box	Pole Mount	Junction Box	Corner Mount
DA-JB4150	DA-LM2000	DA-JB2400	DA-RM2000

# ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-T4537HRXA	POLE	 <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">JUNCTION BOX</span> Model: DA-JB4150
		<div style="text-align: center;">+</div>  <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">POLE MOUNT</span> Model: DA-LM2000
		or
		 <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">JUNCTION BOX</span> Model: DA-JB2400
	<div style="text-align: center;">+</div>  <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">POLE MOUNT</span> Model: DA-LM2000	
	CORNER	 <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">JUNCTION BOX</span> Model: DA-JB4150
		<div style="text-align: center;">+</div>  <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">CORNER MOUNT</span> Model: DA-RM2000
		or
		 <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">JUNCTION BOX</span> Model: DA-JB2400
		<div style="text-align: center;">+</div>  <span style="background-color: #00A0C0; color: white; padding: 2px 5px;">CORNER MOUNT</span> Model: DA-RM2000