



## CPS1215RM Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 10-outlet rack mount power distribution unit (PDU) provides 120V 15A output. It distributes power to 10 NEMA 5-15R receptacles from a single NEMA 5-15P input, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a durable metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray and is ETL/RoHS certified.

A Three-Year Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

### Typical Applications

- Servers
- Network Devices
- Telecom Equipment

### Features

- Basic PDU
- Industrial-Grade Metal Housing
- 3-Year Warranty

# CPS1215RM Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

GENERAL	
Type	Basic PDU
Phase	Single Phase
INPUT	
Voltage	120V
Switch	Lighted On/Off
Current	15A max
Frequency	60Hz
Plug Type	NEMA 5-15P
Cord Length	15'
OUTPUT	
Nominal Output Voltage	120V
Outlets - Total	10
Outlet Type	NEMA 5-15R
Outlets - Front	0
Outlets - Rear	10
Overload Protection	15A
PHYSICAL	
Rack Size	1U
Cord Retention Organizers	Yes
Dimensions (WxHxD) (in.)	17.25 x 1.75 x 4.75
Weight (lbs.)	5.0
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Relative Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL Recognized
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited