

GPRS Consumption Monitoring App

APPLICATION NOTE

Videofied[®] alarm systems controlled by Monitoring smartphone App use a SIM card to send information to the App server.

Alarm panel transmissions when used with Monitoring smartphone App

On average, an alarm panel used with the Monitoring App transmits the following data:

- 1 periodic test per day, sent to the monitoring station.
- 2 Arming/Disarming notifications per day, sent to the monitoring station and/or to the users smartphones (optional, the parameter must be enabled in the panel setup).
- 3 video alarms per month, sent to the monitoring station.
- 2 connections per day from a user smartphone to the panel.
- 30 snapshots per month from the user smartphone.

	GPRS per event (ko)	Monthly scenario (occurrences)	Monthly average GPRS consumption (ko)
Periodic test	1.7	31	52.7
Arm/Disarm (Security)	4	60	240
Arm/Disarm (Comfort)	4	60	240
Intrusion with video	250	3	750
Connection from a user smartphone to the panel	4	60	240
Snapshot	28	30	840
		Total	2362 ko

EMEA SALES

23, avenue du Général Leclerc 92340 BOURG-LA-REINE FRANCE E-Mail : emeasales@rsivideotech.com 1375 Willow Lake Blvd, Suite 103 Vadnais Heights, MN 55110

USA

E-Mail: usasales@rsivideotech.com

North American Headquarters

