



BCT6L9N225 | 3-PHASE MODULAR UPS BATTERY CABINET

Configure a new system or extend runtime capacity with an additional battery cabinet

The CyberPower BCT6L9N225 3-Phase Modular UPS Battery Cabinet can hold up to 12 battery modules (BM120V30ATY). These 6-layer units can be configured as stand-alone cabinets, rack mounted, or stacked with another component of our modular UPS system. Includes a One-Year Limited Warranty.



SPECIFICATIONS

BATTERY	
Battery Module Capacity Maximum	12
OUTPUT	
Nominal Output Voltage	240 VAC
PHYSICAL	
Color	Black
Form Factor	Modular
Material of Construction	Metal
Mounting Hardware	Yes
POWER MODULE DIMENSIONS	
Battery Module	3U
Battery Cabinet - Rack Units	19U

PHYSICAL DIMENSIONS	
Physical Dimensions - WxHxD (cm)	48.51 x 94.23 x 77.47 cm
Physical Dimensions - WxHxD (in.)	19.1 x 37.1 x 30.5 in.
Weight (kg)	93.89 kg
Weight (lb)	207 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	63.2 x 112.09 x 101.6 cm
Shipping Dimensions - WxHxD (in.)	24.88 x 44.13 x 40 in.
Weight (kg)	141.52 kg
Weight (lb)	312 lbs.

BCT6L9N225

3-PHASE MODULAR UPS BATTERY CABINET

SPECIFICATIONS CONT.

ENVIRONMENTAL

Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Elevation Note	At \leq 1,000m above sea level, de-rate power by 1% per 100m between 1,000m and 3,048m
Operating Relative Humidity	0 - 95 % (non-condensing)
Operating Temperature	32 - 104°F (0 - 40°C)
Operating Temperature Note	Battery life is halved for every 50°F (10°C) increase above 68°F (20°C)
Storage Battery Temperature Note	Optimum battery storage between 5 - 68°F (-15 - 20°C)
Storage Relative Humidity	0 - 95% (non-condensing)
Storage Temperature	5 - 104°F (-15 - 40°C)

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	cTUVus UL1778, CSA C22.2 No. 107.3-14 CFR 47 FCC Part 15, Subpart B, Class A

WARRANTY

Product Warranty	One-Year Limited Warranty
------------------	---------------------------