



SMUCB175UAC | 3-PHASE MODULAR UPS CIRCUIT BREAKER

Ensure safe operation for your equipment and personnel with proper over-current protection

The CyberPower SMUCB175UAC 3-Phase Modular UPS Circuit Breaker Hardware provides convenience and safety with optional 40KVA UPS Input/Output. If the input side overcurrent protection device is in a different area of your facility, having the input circuit breaker at the UPS adds an extra disconnect point for easy bypass during repairs or maintenance. The output circuit breaker also provides protection if your load is connected directly to the UPS without an appropriate overcurrent protection device. Includes a One-Year Limited Warranty.

For CyberPower Smart App Online 3-Phase Modular UPS system SMO40KAMFA.



SPECIFICATIONS

PHYSICAL		ENVIRONMENTAL	
Color	White/Gray	Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Form Factor	Modular	Operating Elevation Note	At $\leq 1,000\text{m}$ above sea level, de-rate power by 1% per 100m between 1,000m and 3,048m
Material of Construction	Metal	Operating Relative Humidity	0 - 95 % (non-condensing)
Mounting Hardware	Yes	Operating Temperature	32 - 104°F (0 - 40°C)
PHYSICAL DIMENSIONS		Operating Temperature Note	Battery life is halved for every 50°F (10°C) increase above 68°F (20°C)
Physical Dimensions - WxHxD (cm)	7.62 x 19.05 x 8.64 cm	Storage Battery Temperature Note	Optimum battery storage between 5 - 68°F (-15 - 20°C)
Physical Dimensions - WxHxD (in.)	3.00 x 7.5 x 3.40 in.	Storage Relative Humidity	0 - 95% (non-condensing)
Weight (kg)	2.0 kg	Storage Temperature	-4 - 158 °F (-20 - 70 °C)
Weight (lb)	4.40 lbs.	CERTIFICATIONS	
SHIPPING DIMENSIONS		Environmental	RoHS Compliant
Shipping Dimensions - WxHxD (cm)	11.43 x 12.7 x 20.02 cm	Safety	UL489/CSA C22.2/CE CCC IEC 60947-1 IEC 60947-2 EN 50581
Shipping Dimensions - WxHxD (in.)	4.5 x 5 x 7.88 in.	WARRANTY	
Weight (kg)	2.0 kg	Product Warranty	One-Year Limited Warranty
Weight (lb)	4.40 lbs.		