

NEW

Safety Accident Prevention

IDIS Speaker Bracket

Information speaker for everyone's safety



Easy Installation

Combining camera and speaker without additional perforation and wiring work



Strong Output

Hi-Fi audio amplifier and up to 110 dB output
Wide-range announcements through a powerful combination of piezo speakers



Equipped with spider repellent function

25~30KHz variable frequency generation
365 days clear picture quality through spider repellent function




IDIS Speaker Bracket | Safety accident prevention

Provides announcements to prevent various safety accidents, and efficiently utilizes space by combining with a camera without requiring a separate installation place or work. The camera and PoE connection eliminates the need for separate wiring work, and secures clear picture quality 365 days a year through the spider repellent function.

✓ Safety management with clear sound quality and picture quality

- Prevent safety accidents with voice guidance
- Clear Audio output
- Space-saving speaker bracket
- PoE connectivity with no extra wiring required
- Support for mounting various cameras
- Guaranteed picture quality from spiders or small insects



Application Cases



Corridor / Aisle monitoring

Corridors that may be crowded or a relatively narrow aisle
Schools, Building Corridors
Outdoor Streets




Outdoor Cobweb prevention

Prevention of obstacles in front of the lens caused by spiders and small insects



Outdoor eaves

Outdoor eaves installation, rainproof performance ensures reliable audio output even outdoors





< Schools and Buildings >




When an event occurs

When an event occurs, it is possible to broadcast information or play a sound source


IDIS Speaker Bracket Instruction guide




Screw-in point for Camera mount




DC-D1642RX




DC-D3642RX



DC-Y166CWRX



DC-S6162X



PoE Speaker embeded Wall mount (Built-in ultrasonic spider repellent)

DA-WM2250

- PoE Speaker embeded
- Built-in ultrasonic spider repellent
- Hi-Fi sound quality
- 2 Ch. Stereo audio
- Embeded PoE extender
- Available for various type of Camera
- Optimize Terminal video block connection




SPECIFICATIONS


Spider repellent frequency generator (25~30KHz)	Size	38x38mm
	Max. Output Voltage	30Vp-p
	Voltage	DC12V 150mA
	Frequency	25~30KHz Variable Frequency
	Ultrasonic Output	Max. 30Vp-p
	Max. Output dB	110dB
	Max. Input Voltage	150Vp-p
Amplifier	Sound Quality	HI-FI
	Amplifier Output	15W
	Compatible Speaker	10W-60W, 4Ω- 8Ω
	Sound Channel	1CH Mono
	Sound Output	12V - 8Ω Speaker/12W 12V - 4Ω Speaker/20W
	Operative Temperature	-50°C to 50°C
PoE Splitter	Input Voltage	PoE 802.3at (Class 4), PoE 802.1af
	Variable Input Voltage	PoE (DC 36~57V)
Others	Audible Speaker	12.5W
	Housing	Metal, Diameter 180mm, Waterproof for Outdoors
	Camera Compatibility	Compatible will all IDIS Dome and Fisheye Cameras

APPEARANCE


(Unit – mm)



SPCC 1.0T



SPCC 1.0T



EGI 2.0T

Compatible cameras for IDIS Speaker Bracket

Camera List	
DC-D3745RXA	H.265 5MP AI IR Dome Camera IDIS AI Engine (IDLA) equipped camera
DC-D3745HRXA	H.265 5MP AI IR Dome Camera (Built-in Heater) IDIS AI Engine (IDLA) equipped camera
DC-D3645RX	Base Line 5MP IR Dome Camera Motorized varifocal lens (f=3.0-13.5mm)
DC-D3645HRX	Base Line 5MP Vandal IR Dome Camera (Built-in Heater) Motorized varifocal lens (f=3.0-13.5mm)
DC-D3642WRX	Base Line Full-HD Vandal IR Dome Camera Motorized varifocal lens (f=2.8-12mm)
DC-D3642RX	Base Line Full-HD IR Dome Camera Motorized varifocal lens (f=2.8-12mm)
DC-D3642HRX	Base Line Full-HD Vandal IR Dome Camera (Built-in Heater) Motorized varifocal lens (f=2.8-12mm)
DC-D3148HRX	Base Line 4K Vandal IR Dome Camera (Built-in Heater) Motorized varifocal lens (f=2.7-13.5mm)
DC-D1645WRX	Base Line 5MP Vandal IR Dome Camera Fixed focus lens (f=2.8mm / 4.0mm)
DC-D1642WRX	Base Line Full-HD Vandal IR Dome Camera Fixed focus lens (f=2.8mm)
DC-D1642RX	Base Line Full-HD IR Dome Camera Fixed focus lens (f=2.8mm / 4.0mm)
DC-D1148WRX	Base Line 4K Vandal IR Dome Camera Fixed focus lens (f=3.3mm)
DC-D1142CRX	Full-HD IR Micro Dome Camera Fixed focus lens (f=2.8mm)
DC-Y166CWRX	12MP IR Fisheye Camera 360 Degree VR Camera
DC-Y1665WRX	5MP IR Fisheye Camera 360 Degree VR Camera

