

# Full HD IR Bullet Camera

## DC-T4217WRX 2.8mm | 4.0mm | 6.0mm

- Easy Installation with DirectIP NVR
- Full HD (1080p) Resolution
- Fixed-focal Lens (f = 2.8 mm / 4.0 mm / 6.0mm)
- IK10 / IP66 Supports
- PoE (IEEE 802.3af Class 2)
- Day and Night (ICR)
- True Wide Dynamic Range (WDR)
- IR LED (Distance : 20 m / 65.6 ft)
- 3-axis Mechanical Design for Installation
- Supports ONVIF



### SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f = 2.8 mm / 4.0 mm / 6.0mm
Aperture	F2.0 (2.8 mm) / F 1.6 (4.0 mm / 6.0mm)
Iris Control	Fixed IRIS
Angular Field of View	111.6°(H), 61.45°(V), 127.3°(D) (f = 2.8 mm) 87.4°(H), 46.9°(V), 103.5°(D) (f = 4.0 mm) 53.5°(H), 29.5°(V), 62.1°(D) (f=6.0mm)
Min. Illumination	Color : 0.1 Lux @ F2.0, B/W : 0 Lux (IR LED On) (2.8 mm) Color : 0.07 Lux @ F1.6, B/W : 0 Lux (IR LED On) (4.0 mm / 6.0mm)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	IR Cut Filter with Auto Switch
IR Distance (LEDs)	20 m / 65.6 ft (2 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Digital Noise Reduction	Configurable 2DNR / 3DNR
Backlight Compensation	On / Off
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	-
De-fog	-
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - CBR / VBR H.264 - CBR / VBR
Audio Compression	-
Two-way Audio	-
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	30ips : 1920 x 1080
Supported Resolution	1920 x 1080, 1280 x 720, 640 x 360, 352 x 240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, Upnp, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer(NLTSec)	Yes (Up to 60MB)
Edge Storage	-
ALARM AND EVENT	
Trigger Event	Motion Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio In / Out	-
Alarm In / Out	-
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting Up at Above 0°C (32°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	PoE (IEEE 802.3af Class 2)
Power Consumption	PoE, IEEE 802.3af (Class 2), 5.4W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	70.1 mm x 65 mm X 182.7 mm (2.75" x 2.56" x 7.2")
Weight	0.340 Kg (0.75 lb)

### DIMENSIONS

(Unit - mm)

