

Electrical Specifications

- | | |
|------------------|------------------|
| • Input Voltage | 12~57 VDC (Max.) |
| • Output Voltage | 12~57 VDC (Max.) |
| • Max. Current | 1.5 A |

Physical Specifications

- | | |
|----------------------|------------------------|
| • Ports | PoE and LAN (2 x RJ45) |
| • Ethernet Data Rate | 10/100 Mbps |
| • Data Pins | 1/2 & 3/6 |
| • Power Pins | 4/5 & 7/8 |
| • DC input | 2.1x 5.5 mm DC jack |
| • LED Indicator | Power |
| • Color | Black |
| • Dimensions | 51 x 25 x 26.5 mm |
| • Weight | 25 g |

Environmental Specifications

- | | |
|-------------------------|-------------------------------|
| • Operating Temperature | 0 °C to +40 °C |
| • Storage Temperature | -20 °C to +65 °C |
| • Operating Humidity | 10 to 80%
(Non-condensing) |
| • Storage Humidity | 5 to 90%
(Non-condensing) |

Connection Diagram



Product Ordering Information

- DC Injector with LED for C1n Series

Contact Us

- Email: sales@altaitechnologies.com

PE-PB-170727

Although Altai has attempted to provide accurate information in these materials, Altai assumes no legal liability for the accuracy and completeness of the information. All specifications are subject to change without notice.