

DS-K1T681DBWX Face Recognition Terminal



Face recognition terminal is a kind of access control device. It can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

- Android 11 operation system
- 8-inch LCD touch screen, 2 MP wide-angle lens
- Face recognition duration < 0.2 s/User, face recognition accuracy rate ≥ 99%
- Built-in M1 card, Felica card, and DESfire card reading module (Presents card on the screen to authenticate)
- Face mask detection
- 100,000 face capacity, 10,000 fingerprint capacity (with fingerprint module), 500,000 card capacity, and 500,000 event capacity
- Supports ISAPI, ISUP 5.0, TCP/IP
- Supports face recognition of single person and multiple people (up to 5 people)
- Recognition distance: 0.3 to 3 m

• Specification

Display	
Screen size	8 inch
Operation method	Capacitive touch screen
Type	IPS
Video	
Lens	2
Resolution	2 MP
FOV	HFOV = 41.5°; VFOV = 75.5°
Audio	
Audio quality	Support noise suppression and echo cancellation
Network	
Wired network	Support
Wi-Fi	2.4 GHz, IEEE802.11b, 802.11g, 802.11n, 802.11d, 802.11e, 802.11h, 802.11i
Interface	
Network interface	1 RJ-45, 10/100/1000 M self-adaptive
Lock control	1
Exit button	1
Door contact input	1
Alarm input	2
Alarm output	1
TAMPER	1
RS-485	1,RS-485 (Half duplex,HIKVISION)
RS-232	Reserved
Wiegand	1 Wiegand(Hik 26bit,Hik 34bit)
USB	2, one (type C) for inserting module or data transmission, the other (type A) for data transmission
Audio output interface	1 (3.5 mm)
Capacity	
Captured picture capacity	100,000
Authentication	
Card type	M1 card,DESfire card,Felica card
Card presenting mode	Under screen
General	
Power supply	12 VDC, 3 A/24 VDC, 1.5 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	0 to 90% (no condensing)
Anti-corrosion	48H (About 2 years protection)
Headquarters Dimensions	232.5 mm × 29.1 mm × 26.5 mm (9.2" × 1.1" × 1.0")
Hangzhou 310051, China T +86-571-8807-5998 Weight Hikvision.com	Gross Weight: 1.06 kg (2.34 lb) Net Weight: 0.57 kg (1.26 lb)
Follow us on social media to get the latest product and solution information.	
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Japanese, Korean, and Traditional Chinese




Function	
Configuration via Web browser	Support
Hik-Connect	Support operation via mobile application
Video intercom	Support
QR code recognition	Support (with QR code module)
Face anti-spoofing	Support
Face mask recognition	Support

▪ Available Model











DS-K1T681DBWX

▪ Dimension



▪ Accessory

▪ Optional

DS-KAB6-ZU1 Brackets for face terminals	DS-KAB681-QR Peripheral Module	DS-KAB681-F Peripheral Module	DS-KAB681-QRF Peripheral Module	DS-KAB6-W1 Bracket
Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8787-5998 www.hikvision.com Follow us on social media to get the latest product information				
 HikvisionHQ	 HikvisionHQ	 HikvisionHQ	 Hikvision_Global	 Hikvision Corporate Channel
				 hikvisionhq

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq