

DS-K3BC430LX Pro Swing Gates



- Access board is optional, need ordered separately.
- The device supports memory mode, which can realize continuous and fast passage;
- The device has a fire alarm linkage interface. When the signal is triggered, the door wing will automatically open to quickly guide personnel to evacuate;
- It supports power-off passage, and the door wing is in a free state when the power is off, which is convenient for personnel to pass through and prevent panic.
- (Modular installation) Support QR code function, by embedded installation, QR code and card reader combined into one layout is simple and overall.
- (Modular installation) Optional super capacitor to realize automatic door opening when power off;

▪ Specification

System	
Motor	Brushless motor
MCBF	≥ 6 Millions
Operating system	Linux system
Network	
Communication protocol	ISAPI
Wired network	10/100 Mbps self-adaptive Ethernet
Wi-Fi	NA
Interface	
Exit button	1
USB	1
Fire alarm input	1
Hardware	
Access controller	Optional
Supercapacitor	Support
Network switch	Not Support
Power supply for face recognition module	Not Support
Keyfob	Support, need order separately
Card receiver	Optional
Function	
Configuration via Web browser	Support
Configuration via mobile Web browser	Not Support
Audio prompt	Support
AP mode	Not Support
General	
Throughput	30 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method
IR light detectors	Not Support
Lane width	For pairs mode: 550 to 1400 mm (Gap 50 mm, Door wing height 950 mm) 900 mm (Gap 50 mm, Door wing height 1800 mm) For single mode: 650~900 mm (Gap 50 mm, Door wing height 950 mm)
Distance between barrier and ground	950mm to 1800mm
Barrier material	Acrylic glass or Tempered glass
Pedestal material	SUS304 stainless steel with the thickness of 2 mm (0.08")
Indicator	Support
Power	100 to 240 VAC; 50 to 60 Hz
Power consumption	36W (stand by)
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)

Working humidity	10% to 95% (No Condensing)
Dimensions	180 mm x 180 mm x 975 mm (7.09' x 7.09' x 38.39')
Weight	(Net) Left: 30 kg (66.14 lbs) (Rough) Left: 35 kg (77.16 lbs)
Approval	CE/CB/CE-LVD/RoHS/REACH/WEEE
Buzzer	Support
Brake	Support

▪ Available Model

DS-K3BC430LX

▪ Accessory**▪ Optional****DS-K3M210**

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

