## **DTK-2MHLPB Series**

Voice, Data and Signaling Circuit Modular Surge Protection





**DITEK's DTK-2MHLPB** series of signal, data and loop circuit surge protectors provide robust protection in a compact package. This series was designed for ease of installation, with convenient field-replaceable modules and a Snap-Track base system, allowing the installer to protect multiple circuits while utilizing a common ground point.

Technical Specifications						
DTK-2MHLP	5B	12B	24B	36B	48B	75B
Service Voltage:	5V	12V	24V	36V	48V	75V
MCOV:	6V	18V	33V	48V	64V	90V
Clamping Voltage:	6.8V	21.6V	39V	57V	76V	108V
Protection Modes:		I	_ine-Gro	ound (Al	l)	
Surge Current Rating:	20,000 Amps					
Max Continuous Current:	5 Amps					
Data Rate:	200kbps to 2Mbps					

### **Product Features**

- Protects two pairs per module
- Multi-stage, SAD technology, hybrid design, provides the best possible protection
- Field replaceable, modular edge card connection design with a single point ground for fast installation, saves time
- Six voltage levels available to protect all types of voice/data applications
- Hard-wired multi-base mounting system allows you to protect up to ten pairs with a common ground. See next page for base part numbers
- Suitable for use on both AC and DC circuits

#### **Applications**

- Fire Alarm Panel NAC, SLC, PIV and IDC Circuits
- Burglar Alarm Panels NAC and IDC Circuits
- 4-20mA Current Loops

#### **Accessories**

- To order Module with Base, add "WB" to end of part number
- Test Module Kit Part Number DTK-2MHLPTM
- DIN Rail Mounting Kit Part Number DTK-DRK

#### **Mechanical Characteristics**

Base Connection Method:	10AWG max screw terminals			
Module Connection Method:	Edge card into mounting base			
Housing:	ABS			
Operating Temperature:	-40°F - 158°F (-40°C - 70°C)			
Maximum Humidity:	95% non-condensing			
Dimensions:	<b>Module</b> 2.1"L x 1.4W x 1.9"H (53mm x 36mm x48mm)	<b>Module with Base</b> 3.25L" x 1.5"W x 2.6"H (83mm x 38mm x 66mm)		
Weight:	1.2 oz (34g)	2.8 oz (79g)		

#### **Quality, Standards & Approval**

Agency Approvals:	UL497B
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.









# **DTK-2MHLP Series**

Voice, Data and Signaling Circuit Modular Surge Protection




#### **Base Part Numbers and Dimensions**


Part Number	# Pairs Protected	Dimensions
DTK-MB10	2	3.25"H x 1.50"W (82.5mm x 38.1mm)
DTK-2MB	4	3.25"H x 3.00"W (82.5mm x 76.2mm)
DTK-3MB	6	3.25"H x 4.50"W (82.5mm x 114.3mm)
DTK- 4MB	8	3.25"H x 6.00"W (82.5mm x 152.4mm)
DTK- 5MB	10	3.25"H x 7.50"W (82.5mm x 190.5mm)




DTK-MB10








DTK-3MB



DTK-4MB



DTK-5MB