

## 14 AWG 2 Solid Conductors Riser

Part Number: 4313

**Ratings** FPLR, CL3R, FT4, Sunlight Resistant  
**Approvals** UL Listed

### Construction

Conductor Type 14 AWG Solid Bare Copper  
Conductor Count 2  
Insulation Colors Black, Red  
Insulation Type Polypropylene  
Insulation Thickness 0.008" nom.  
Cable Lay Length 5.25" nom.  
Shielding N/A  
Rip Cord Yes  
Jacket Material PVC  
Jacket Thickness 0.015" nom.  
Overall Outer Diameter 0.196" nom.  
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)  
Print Legend HONEYWELL P/N 4313 2C 14AWG E175105 (UL) FPLR OR CL3R FT4 SUN RES 75C (RoHS) W/O#  
XXXXXX-XXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

### Electrical & Environmental

Temperature -20°C to 75°C  
Voltage 300V max.  
Capacitance 24.1 pF/ft. nom.  
Impedance 63 Ohms nom.  
DC Resistance 2.57 Ohms/1000' at 20°C  
RoHS Compliant Yes