



Overview

AL1012ULXPD16 is a multi-output power supply/charger that converts a 115VAC 60Hz input into sixteen (16) 12VDC non power-limited outputs.

Specifications

Input:

- Input 115VAC, 60Hz, 2.6 amp.
- Input fuse rated @ 5 amp/250V.

Output:

- 12VDC output.
- 10 amp continuous supply current.
- Sixteen (16) fuse protected outputs.
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.7 amp.

Supervision:

- AC fail supervision (form “C” contacts).
 - Notification trigger is selectable for 30 seconds (factory set) or 6 hours.
- Low battery supervision (form “C” contacts).
- Battery presence supervision (form “C” contacts).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 61.42 BTU/Hr.
- System AC input VA requirement: 299VA.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 15.5” x 12” x 4.5” (393.7mm x 304.8mm x 114.3mm)
 - Accommodates one (1) 12VDC/12AH batteries.
- Product weight (approx.): 11.2 lbs. (5.08 kg).
- Shipping weight (approx.): 12.1 lbs. (5.49 kg).

Agency Approvals



UL 294 UL Listed for Access Control System Units.



General Signaling Equipment
Evaluated to CSA Standard C22.2 No.205-M1983

Enclosure Dimensions (H x W x D approximate):
 15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)

