



# 12.8V 120AH LITHIUM BATTERY



## ► Features

- A grade brand new prismatic LiFePO4 cells
- Over charge, over discharge, over temperature, low Temperature, over current and short circuit protection
- Cell balance function
- Certificate: UN38.3, MSDS
- $\geq 4000$  cycles @80% DOD(25°C, 0.5C )
- Easy installation and maintenance free
- IP65, superior safety
- Max.4 battery packs can be connected in series

## ► Electrical Characteristics

Model	LFP120EP12.8
Battery Type	LiFePO4
Nominal Voltage (V)	12.8
Nominal Capacity (AH)	120
Energy (WH)	1536
Pack Mode	4S1P
Continuous Discharge Current (A)	60
Charge Cut-off Voltage (V)	14.4
Discharge Cut-off Voltage (V)	10.4
Max.Charge Current (A)	50
Max.Discharge Current (A)	100
Peak Discharge Current (A)	130@10S
Recommend Discharge Current (A)	60
Recommend Discharge Depth (%)	80
Cycle Life	$\geq 4000$ cycles (25°C, 0.5C ) 80% DOD
Communication	—
Charge&Discharge Temperature (°C)	Charge: 0°C~+55°C / Discharge: -20°C~+60°C
Optimal Storage Temperature (°C)	5°C ~ +35°C
Recommend Storage Humidity	20%~80%
Terminal	M8
Dimensions (L*W*H) (mm)	339*185*218
Weight (Kg)	19±0.5
Transportation	UN38.3, MSDS
IP Class	IP65