

# CS-H8c Pro (2K)

Smart Home Camera - Outdoor PT Camera



## Introduction

EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ, you can watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.

## Main Features



2K Resolution



AI-Powered Human Detection



Color Night Vision



Smart Tracking



Two-Way talk



Weatherproof Design



360° Panoramic View



H.265 Video Compression

## Dimensions



# Specifications

|                                       |                                                                                                                                                         |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                          | CS-H8c Pro (2K)                                                                                                                                         |
| <b>Camera</b>                         |                                                                                                                                                         |
| <b>Image sensor</b>                   | 1/2.8" Progressive Scan CMOS                                                                                                                            |
| <b>Shutter Speed</b>                  | Self-adaptive shutter                                                                                                                                   |
| <b>Lens</b>                           | 4mm@ F1.6, viewing angle: 49° (Vertica), 89° (Horizontal), 104° (Diagonal)<br>6mm@ F1.6, viewing angle: 28° (Vertica), 52° (Horizontal), 60° (Diagonal) |
| <b>PT Angle</b>                       | Pan: 350° , Tilt: 80°                                                                                                                                   |
| <b>Minimum Illumination</b>           | 0.5 Lux @(F1.6, AGC ON), 0 Lux with IR (* data is obtained from EZVIZ laboratories)                                                                     |
| <b>Lens Mount</b>                     | M12                                                                                                                                                     |
| <b>Day &amp; Night</b>                | IR-cut filter with auto switch                                                                                                                          |
| <b>DNR</b>                            | 3D DNR                                                                                                                                                  |
| <b>WDR</b>                            | Digital WDR                                                                                                                                             |
| <b>Black &amp; White Night Vision</b> | 30m/98ft                                                                                                                                                |
| <b>Video &amp; Audio</b>              |                                                                                                                                                         |
| <b>Max. Resolution</b>                | 2304*1296                                                                                                                                               |
| <b>Frame Rate</b>                     | Max : 30fps; Self-Adaptive during network transmission                                                                                                  |
| <b>Video Compression</b>              | H.265 / H.264                                                                                                                                           |
| <b>H.265 Type</b>                     | Main Profile                                                                                                                                            |
| <b>Video Bit Rate</b>                 | Ultra-HD; Hi-Def; Standard. Adaptive bit rate.                                                                                                          |
| <b>Audio Bit Rate</b>                 | Self-Adaptive                                                                                                                                           |
| <b>Network</b>                        |                                                                                                                                                         |
| <b>Wi-Fi Standard</b>                 | IEEE802.11b, 802.11g, 802.11n                                                                                                                           |
| <b>Frequency Range</b>                | 2.4 GHz ~ 2.4835 GHz                                                                                                                                    |
| <b>Channel Bandwidth</b>              | Support 20MHz                                                                                                                                           |
| <b>Security</b>                       | WPA-PSK/WPA2-PSK                                                                                                                                        |
| <b>Transmission Rate</b>              | 11b: 11Mbps,11g :54Mbps,11n :72Mbps                                                                                                                     |
| <b>Wi-Fi Pairing</b>                  | AP pairing                                                                                                                                              |
| <b>Protocol</b>                       | EZVIZ cloud proprietary protocol                                                                                                                        |
| <b>Interface Protocol</b>             | EZVIZ cloud proprietary protocol                                                                                                                        |
| <b>Wired Network</b>                  | RJ45 × 1 (10M/100M Adaptive Ethernet Port)                                                                                                              |
| <b>Function</b>                       |                                                                                                                                                         |
| <b>Smart Alarm</b>                    | AI Human Detection                                                                                                                                      |
| <b>Auto Tracking</b>                  | Supports                                                                                                                                                |
| <b>Customized Alert Area</b>          | Supports                                                                                                                                                |
| <b>Two-way Talk</b>                   | Supports                                                                                                                                                |
| <b>Preset Locations</b>               | Supports                                                                                                                                                |
| <b>General Function</b>               | Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark                                                                                   |
| <b>Storage</b>                        |                                                                                                                                                         |
| <b>Local Storage</b>                  | Micro SD card slot (Up to 512GB)                                                                                                                        |
| <b>Cloud Storage</b>                  | EZVIZ Cloud Storage                                                                                                                                     |
| <b>General</b>                        |                                                                                                                                                         |
| <b>Operating Conditions</b>           | -30°C to 50°C ( -22 °F to 122 °F )<br>humidity 95% or less (non-condensing)                                                                             |
| <b>IP Grade</b>                       | Weatherproof Design                                                                                                                                     |
| <b>Power Supply</b>                   | DC 12V/1A                                                                                                                                               |
| <b>Power Consumption</b>              | MAX. 12W                                                                                                                                                |
| <b>Dimensions</b>                     | 100× 136 × 140mm (3.94 × 5.35× 5.51inch)                                                                                                                |
| <b>Packaging Dimensions</b>           | 140*140*192mm (5.51 ×5.51× 7.56inch)                                                                                                                    |
| <b>Weight</b>                         | Net Weight: 516g<br>With Package: 820.5g For EU Standard Version                                                                                        |