

DVR-208U-M1 TURBO ACUSENSE DVR

Key Feature

- Deep learning based human and vehicle targets classification of Motion Detection 2.0
- 8 analog channels and 1 HDD 1U DVR
- Efficient H.265 Pro+ compression technology
- 5 MP@12 fps encoding capability
- HDTVI/AHD/CVI/CVBS/IP video inputs
- Up to 16 network cameras can be connected



Smart Function

- Deep learning based human and vehicle targets classification of Motion Detection 2.0

Compression and Recording

- H.265 Pro+ video compression improves encoding efficiency, and reduces data storage costs

Storage and Playback

- 1 SATA interface (up to 10 TB capacity)
- Smart search for efficient playback

Network & Ethernet Access

- Compatible with major Wi-Fi dongle products in the market
- HiLookVision & DDNS (Dynamic Domain Name System) for easy network management

▪ Specification


| Motion Detection 2.0 | |
|-----------------------------|---|
| Human/Vehicle Analysis | <p>Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;</p> <p>Quick search by object or event type is supported;</p> |
| Recording | |
| Video Compression | H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 |
| Encoding Resolution | 8 MP/5 MP/3K/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF |
| Frame Rate | <p>Main stream: 3K@12 fps/5 MP@12 fps/4 MP@15 fps/8 MP Lite@15 fps/3 MP@18 fps 1080p/720p /WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N)</p> <p>Sub-stream: WD1/4CIF/CIF@25 fps (P)/30 fps (N)</p> |
| Video Bitrate | 32 Kbps to 10 Mbps |
| Dual-stream | Support |
| Stream Type | Video, Video & Audio |
| Audio Compression | G.711u |
| Audio Bitrate | 64 Kbps |
| Video and Audio | |
| IP Video Input | <p>4-ch (up to 12-ch)</p> <p>Enhanced IP mode on: 8-ch (up to 16-ch), each up to 4 Mbps</p> <p>Up to 8 MP resolution</p> <p>Support H.265+/H.265/H.264+/H.264 IP cameras</p> |
| Analog Video Input | <p>8-ch;</p> <p>BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection</p> |
| HDTVI Input | <p>3K@20 fps, 5 MP@20 fps, 5 MP@12 fps, 4 MP@30 fps, 4 MP@25 fps, 3 MP@18 fps, 1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps</p> |
| AHD Input | <p>5 MP@20 fps, 5 MP@12 fps, 4 MP@30 fps, 4 MP@25 fps, 1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps</p> |
| HDCVI Input | <p>5 MP@20 fps, 4 MP@30 fps, 4 MP@25 fps, 1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps</p> |
| CVBS Input | PAL/NTSC |
| HDMI Output | 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz |
| VGA Output | 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz |

| | |
|----------------------------|---|
| Video Output Mode | HDMI/VGA simultaneous output |
| Audio Input | 1-ch, RCA (2.0 Vp-p, 1 K Ω) 4-ch via coaxial cable |
| Audio Output | 1-ch, RCA (Linear, 1 K Ω) |
| Two-Way Audio | 1-ch, RCA (2.0 Vp-p, 1 K Ω) (using the audio input) |
| Synchronous playback | 8-ch |
| Network | |
| Total Bandwidth | 128 Mbps |
| Network Protocol | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF |
| Remote Connection | 64 |
| Network Interface | 1, RJ45 10/100/1000 Mbps self-adaptive Ethernet interface |
| Wi-Fi | Connectable to Wi-Fi network by Wi-Fi dongle through USB interface |
| Auxiliary Interface | |
| SATA | 1 SATA interface |
| Capacity | Up to 10 TB capacity for each disk |
| USB Interface | Rear panel: 2 × USB 2.0 |
| General | |
| Power Supply | 12 VDC, 2 A |
| Consumption | ≤ 10 W (without HDD) |
| Working Temperature | -10 °C to +55 °C (+14 °F to +131 °F) |
| Working Humidity | 10% to 90% |
| Dimension (W × D × H) | 265 × 225 × 48 mm (10.4 × 8.9 × 1.9 inch) |
| Weight | ≤ 1.6 kg (without HDD, 3.5 lb.) |

Note:

Enhanced IP mode might be conflicted with smart events (motion detection 2.0 and perimeter protection) or other functions, please refer to the user manual for details.

Physical Interface



| No. | Description | No. | Description |
|-----|----------------------------|-----|---|
| 1 | Video and coaxial audio in | 5 | AUDIO IN, RCA connector |
| 2 | HDMI interface | 6 | LAN network interface and USB interface |
| 3 | VGA interface | 7 | 12 VDC power input |
| 4 | AUDIO OUT, RCA connector | 8 | GND |

Available Model

DVR-208U-M1



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq