



<b>Parameters technical</b>	<b>TT592</b>
<b>Transmission protocol</b>	ipcolor
<b>Delay</b>	Zero delay
<b>Transmission method</b>	CAT5/CAT5E/CAT6 Cable
<b>Connection mode</b>	One to one/One to many/Switch cascade
<b>HDMI signal</b>	HDMI 2.0 compatible with HDCP2.2
<b>Resolution</b>	720P@50/60Hz, 1080P@24/2 /50/60Hz, 1080i@50/60Hz, 1024*768@60Hz, 1280*768@60Hz, 1280*800@60Hz, 1280*960@60Hz, 1280*1024@60Hz, 1440*900@60Hz, 1400*1050@60Hz, 1600*900@60Hz, 1600*1200@60Hz, 1680*1050@60Hz, 1920*1080@60Hz, 1920*1200@60Hz, 2560*1440@60Hz, 2560*1600@60Hz, 3840*2160 @24/25/30/50/60/23.9/29.9/ 59.9Hz, 4096*2160 @24/25/30/50/60/23.9 /29.9/ 59.9Hz
<b>Transmission Distance</b>	≤100m
<b>Audio format</b>	LPCM 7.1/DTS-HD/DTS-Audio/Dolby Digital plus/Dolby TrueHD/Dolby Digital/Dolby Atmos
<b>Audio separation</b>	Support RX S/PDIF audio separation
<b>Bi-directional IR</b>	Support bi-directional IR pass back, Support 20-60khz IR devices
<b>ARC</b>	Support ARC back to TX
<b>HDMI loop out</b>	Support TX loop out of HDMI
<b>CEC</b>	Support CEC control
<b>EDID</b>	Support EDID passthrough
<b>Working Temperature</b>	-20~60°C
<b>Storage Temperature</b>	-30~70°C
<b>Protection</b>	ESD protection, surge protection, lightning protection
<b>Humidity (no condensation)</b>	0~90%
<b>Power supply</b>	5V/2A
<b>Dimension</b>	123.95(L)*115.20(W)*28.00(H)mm