

Especificaciones

| | |
|-----------------------------------|--|
| Type | Standard, Master |
| Style | LC, SC, ST, FC, MU, DIN, D4, MPO, SC/APC, FC/APC, LC/APC, MU/APC |
| Fiber | Singlemode/Multimode 50/125, 62.5/125 (Multimode) OM2&OM1 50/125, 10G (Multimode) OM3 |
| Cable | Simplex, Duplex Φ3.0mm, Φ2.0mm, Φ0.9mm PVC or LSZH |
| Polishing Manner | UPC, SPC, APC (8° & 6°) |
| Insertion Loss | ≤ 0.1dB (For Singlemode Master) ≤ 0.25dB (For Singlemode Standard) ≤ 0.25dB (For Multimode) Tested by JDS RM 3750 |
| Return Loss (Singlemode) | UPC ≥ 50dB SPC ≥ 55dB APC ≥ 60dB (typ. 65dB) Tested by JDS RM3750 |
| Repeatability | ±0.1dB |
| Operating temperature | -40°C to 85°C |
| Geometry Requirement (Singlemode) | Ferrule Endface Radius 7mm ≤ R ≤ 12mm (For APC) 10mm ≤ R ≤ 25mm (For Standard) Apex Offset ≤ 30 μm (For Master) Apex Offset ≤ 50 μm (For Standard) Undercut -50nm ≤ U ≤ 50nm Tested by DORC ZX-1 |

Información Detallada

| | | | |
|-----------------|---|-------------|------------------------|
| Fiber Type | G652D, G657A, G655 | Application | FTTH FTTB FTTX Network |
| Connector Type | LC/SC/FC/ST | Material | PVC/LSZH |
| Product Name | Fiber Optic Patch Cord | Color | Yellow |
| Wavelength | 1310nm Or 1550nm | Fiber Count | Simplex Or Duplex |
| Polish | PC/UPC/APC | Type | Single Mode/Multi-mode |
| Quality Control | 100% Test Before Shipping | Length | 1m 2m 3m Or Customized |
| High Light | fiber patch cord, optical patch cord | | |