

HN-VC06/30/60/120 Volume Controller

- Industrial design and stylish appearance
- Built-in 24V DC forced relay
- Selectable power: 6W, 30W, 60W, 120W
- 5 degree volume control levels
- Applicable to 3-wire, 4-wire and 6-wire systems
- Designed to mount on standard 86 × 86 electrical back box



HN-VC series Volume Controller adopts the advanced 3-wire/4-wire design and it is adaptive to different systems. Four selectable power settings including 6W, 30W, 60W and 120W are available. With an elegant appearance, HN-VC series can easily blend into any aesthetic background.

Technical Specifications

Parameter	Value
HN-VC06	
Dimension (L×W×D)	86 × 86 × 52.5 mm
Rated power	6 W
HN-VC30	
Dimension (L×W×D)	86 × 86 × 67.5 mm
Rated power	30 W
HN-VC60	
Dimension (L×W×D)	86 × 86 × 75.5 mm
Rated power	60 W
HN-VC120	
Dimension (L×W×D)	86 × 86 × 75.5 mm
Rated power	120 W

Other specifications

Input voltage	100V
Frequency response	50 Hz - 20 KHz
Attenuation	5 × 2 dB + off
Current consumption	20 mA , 24V DC
Color	White (RAL 9010)

Ordering Information

Description	Ordering Information
HN-VC06 Volume Controller Rated power: 6W	HN-VC06
HN-VC30 Volume Controller Rated power: 30W	HN-VC30
HN-VC60 Volume Controller Rated power: 60W	HN-VC60
HN-VC120 Volume Controller Rated power: 120W	HN-VC120

Honeywell Audiovisuals

No. 257, Junye Road
Guangzhou GETDD East
510530 China
Tel: +86 20 2839 9600
Fax: +86 20 2820 8706
www.honeywellav.com

1013720011_EN1.1
July 2012
© 2012 Honeywell International Inc.