



A10/A10W SIP mini Intercom

The A10/ A10W SIP mini intercom is designed for indoor scenes with IP54 waterproof and dustproof. Supports wall mounting installation. It combines security, audio intercom and broadcasting functionalities and offers the qualified communication solution for users.

Highlights

- Easy installation and configuration.
- IP54 waterproof and dustproof.
- 20 °C to 50 °C wide range temperature adaptability.
- Built-in 1W speaker and Acoustic Echo Canceller (AEC).
- Built-in 1short circuit input/output interface.
- Functionality including security, intercom and broadcasting.
- Built-in HD camera and with backlight compensation function (for i10V).
- Online management and upgrade.



| Model | Screen | Button | POE | Wifi |
|-------|------------|--------|-----|------|
| A10 | 10/100Mbps | 3 | ☑ | × |
| A10W | 10/100Mbps | 3 | ☑ | ☑ |

Generic

- 2 SIP Lines
- Auto answer
- Intercom function

Intercom Function

- Support customized DSS keys
- Network Time Synchronization
- Action URL / Active URL

Audio

- Narrowband Codec: G.711a/u, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Duplex intercom with Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Networking

- Physical: 10/100 Mbps Ethernet
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static / DHCP / PPPoE
- VPN: L2TP / OpenVPN

- VLAN
- LLDP
- QoS

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- LLDP
- PPPoE
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Firmware Upgrade

- Syslog

- Installation: Indoor installation
- working temperature: -10 ~50 °C
- Storage temperature: -20 ~ 50 °C
- Relative humidity: 10% - 90%
- Qty/CTN: 20 PCS
- N.W/CTN:3.41kg
- G.W/CTN:3.6kg
- Equipment Dimension: 87.56 x 87.56 x 30mm (wall-hung type)
- Equipment Dimension: 87.56 x 87.56 x 21.5mm (in 86 box)
- Packing Dimension: 95x106x40mm
- Outer CTN Dimension: 224x220x210mm (20PCS)
- Equipment weight: 130 g

Physical Specifications

- A10/A10W :3 DSS button (Dial key) (SOS Key) (Hang up key)
- 1 RJ45 port
- 1 short circuit input interface
- 1 relay: NC/NO Contacts, Max DC30V/1A, AC125V/0.5A
- Power: DC12V/1A or POE
- Power Consumption (Adapter): 1.06~2.22W
- Power Consumption (PoE): 1.69~3.68W
- Housing material: ABS

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.
For more information, please visit: www.fanvil.com

www.fanvil.com

Add:10/F Block A, Dualshine Global Science Innovation Center,Honglang North 2nd Road, Bao'an District, Shenzhen, China, 518100

Tel: +86-755-2640-2199 Fax: +86-755-2640-2618 Email: sales@fanvil.com

