HIKVISION

DS-3E2700-HI Switch Series Installation Quick Start

Manual version: 5P101-20231127 BOM: 3104A18J



- This Document includes instructions for using and managing the Product. Pictures, charts, images
 and all other information hereinafter are for description and explanation only.
- The information contained in the Document is subject to change, without notice, due to firmware
 updates or other reasons. Please find the latest version of the Document at the Hikvision website
 (https://www.hikvision.com). Unless otherwise agreed, Hangzhou Hikvision Digital Technology
 Co., Ltd. or its affiliates (hereinafter referred to as "Hikvision") makes no warranties, ex

About this product

This product can only enjoy the after-sales service support in the country or region where the purchase is made.

Acknowledgment of Intellectual Property Rights

- Hikvision owns the copyrights and/or patents related to the technology embodied in the Products
 described in this Document, which may include licenses obtained from third parties.
- Any part of the Document, including text, pictures, graphics, etc., belongs to Hikvision. No part of
 this Document may be excerpted, copied, translated, or modified in whole or in part by any
 means without written permission.
- HIKVISION and other Hikvision's trademarks and logos are the properties of Hikvision in various jurisdictions.
- Other trademarks and logos mentioned are the properties of their respective owners.

LEGAL DISCLAIMER

- TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THIS DOCUMENT AND THE PRODUCT DESCRIBED, WITH ITS HARDWARE, SOFTWARE AND FIRMWARE, ARE PROVIDED "AS IS" AND "WITH ALL FAULTS AND ERRORS". HIKVISION MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY, SATISFACTORY QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. THE USE OF THE PRODUCT BY YOU IS AT YOUR OWN RISK. IN NO EVENT WILL HIKVISION BE LIABLE TO YOU FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES, INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, OR LOSS OF DATA, CORRUPTION OF SYSTEMS, OR LOSS OF DOCUMENTATION, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), PRODUCT LIABILITY, OR OTHERWISE, IN CONNECTION WITH THE USE OF THE PRODUCT, EVEN IF HIKVISION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR LOSS.
- YOU ACKNOWLEDGE THAT THE NATURE OF THE INTERNET PROVIDES FOR INHERENT SECURITY RISKS, AND HIKVISION SHALL NOT TAKE ANY RESPONSIBILITIES FOR ABNORMAL OPERATION,

PRIVACY LEAKAGE OR OTHER DAMAGES RESULTING FROM CYBER-ATTACK, HACKER ATTACK, VIRUS INFECTION, OR OTHER INTERNET SECURITY RISKS; HOWEVER, HIKVISION WILL PROVIDE TIMELY TECHNICAL SUPPORT IF REQUIRED.

YOU AGREE TO USE THIS PRODUCT IN COMPLIANCE WITH ALL APPLICABLE LAWS, AND YOU ARE
SOLELY RESPONSIBLE FOR ENSURING THAT YOUR USE CONFORMS TO THE APPLICABLE LAW.
ESPECIALLY, YOU ARE RESPONSIBLE, FOR USING THIS PRODUCT IN A MANNER THAT DOES NOT
INFRINGE ON THE RIGHTS OF THIRD PARTIES, INCLUDING WITHOUT LIMITATION, RIGHTS OF
PUBLICITY, INTELLECTUAL PROPERTY RIGHTS, OR DATA PROTECTION AND OTHER PRIVACY RIGHTS.
YOU SHALL NOT USE THIS PRODUCT FOR ANY PROHIBITED END-USES, INCL

1	٠	ò	•	ì
۹	٠	٠		•

- This document provides a brief guide for installing HIKVISION DS-3E2700-HI switch series.
 For more installation information, see HIKVISION DS-3E2700-HI Switch Series Installation Guide.
- The figures in this document are for illustration only.

Symbols				
@				
A				



The installation tools are not provided with the switch. Prepare them yourself as required.









Flat-blade screwdriver

Phillips screwdriver

Needle-nose pliers

Marker



ESD wrist strap

Installation accessories









Cage nut (user supplied)

M6 screw (user supplied)

M4 countersunk-head screw

Grounding screw







Console cable

Rubber feet

Mounting brackets



The applicable installation accessories vary by switch model. Some accessories are not provided with the switch. The packing list describes the accessories provided with the switch.



Wear an ESD wrist strap, and make sure the wrist strap makes good skin contact and is reliably grounded.

Mounting the switch in a rack




For the DS-3E2700-HI switch series, you can install the mounting brackets only at the port side.




Four screws are required to attach a mounting bracket.


Attach the mounting brackets to the switch



Attach cage nuts to the rack posts




Mount the switch in the rack



Mounting the switch on a workbench

Attach the rubber feet to the switch bottom









•

Correctly connecting the switch grounding cable is crucial to lightning protection and EMI protection. Use the grounding cable provided with the chassis to ground the switch.

Connect the grounding cable to the switch



Connect the grounding cable to a grounding strip



Connecting the power cord



- Before connecting the power cord, connect the grounding cable and make sure the switch is reliably grounded.
- To avoid bodily injury, connect the power cord first to the switch and then to the power supply system.

