

Compare Backup Cams



Model	MR-1000	MR-C100	MR-C200	MR-C300	MR-S100
Description	Replacement mirror monitor	Rear/front camera	Rear/front camera	Rear camera w/ license plate mount	Parking sensors
TV Modes	---	PAL, NTSC	PAL, NTSC	PAL, NTSC	---
Screen Type	TFT LCD	---	---	---	---
LCD Size	4.3"	---	---	---	---
Video Output	---	RCA Connector 1.0vp-p, 75 ohm	RCA Connector 1.0vp-p, 75 ohm	RCA Connector 1.0vp-p, 75 ohm	---
Video Inputs	AV1 / AV2	---	---	---	---
Resolution	480 x 272	480p	480p	576p (PAL) / 480p (NTSC)	---
Aspect Ratio	16:9	---	---	---	---
Power Supply	DC 12V	DC 12V +/- 10%	DC 12V +/- 10%	DC 12V +/- 10%	10.5V - 15V
Current Draw	0.5W - 3.6W	<120 mA	<120mA	<250mA	<200mA
Operating Temperature	---	-25°C to 65°C	-25°C to 65°C	-25°C to 65°C	-35°C to 85°C
Waterproof	---	IP 68 Standard	IP 68 Standard	IP 68 Standard	IP 68 Standard
Dustproof	---	IP 68 Standard	IP 68 Standard	IP 68 Standard	IP 68 Standard
LED Brightness	---	---	---	27 lm per LED	---
Detection Range	---	---	---	---	1.3ft to 6.7ft
Reliability	---	---	---	---	Automotive Grade
Other Features	Activates with reverse lamp	Auto White Balance	Auto White Balance	Auto White Balance	Parking sensor