

NK-1200

- Remote control of NVRs, network video transmitters, network video receivers and network cameras via network connection
- Control of NVRs by using a USB mouse via network connection
- Two-way audio communication
- Convenient firmware upgrades via either the USB port or ethernet
- Firmware duplication and auto-recovery functions to enhance system stability
- Management of multiple network keyboards via network connection
- Programmable by using the LCD screen
- Supports PoE (IEEE 802.3af class 0)



SPECIFICATIONS

COMMUNICATION	
Interface	2 x RS485 (Terminal Block), 10/100/1000 Ethernet (RJ45, PoE IEEE802.3AF)
Baud Rate	300bps ~ 115,200bps
Supports Protocols	Over 70 sorts of PTZ protocol (IDIS, PANASONIC, PELCO, SAMSUNG, etc.)
Supports Devices	IP Camera, NVR, IDIS solution Suite
Display	LCD (2 Line)
USB	1 x USB2.0, 1 x USB3.0
Audio In / Out	1 (3.5mm) / 1 (3.5mm)
Component	Joystick + Main Control Board
S/W Upgrade	USB, Network
Set-up Program	IDIS Discovery
GENERAL	
Dimensions (W x H x D)	376.9mm x 95mm x 177.6mm (15.0" x 3.7" x 7.0")
Weight	1.2kg (2.64lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Input	DC 48V, 1A, PoE(IEEE 802.3af class 0)
Power Consumption	48V=, 0.18A, 8.64W PoE, IEEE 802.3af(Class 0)
Approvals	FCC, CE, KC