

TABLA DE GRAPAS DE ACERO FORJADO

DIÁMETRO DE CABLE		TABLA GUÍA AP 19B-80			PRESION (TORQUE)	
mm	Pulg.	Número Mínimo de Perros	Espacio de Perros en mm	Longitud de cable doblado Incluyendo el ojo	Kg-m	Lbpie
6.35	1/4	2	61	121	236	15
7.94	5/16	2	67	133	45	30
9.53	3/8	2	83	165	67	45
11.11	7/16	2	89	178	97	65
12.70	1/2	3	97	292	97	65
14.30	9/16	3	102	305	141	95
15.90	5/8	3	102	305	141	95
19.05	3/4	4	114	457	193	130
22.23	7/8	4	121	483	335	225
55.40	1	5	132	660	335	225
28.60	1 1/8	6	144	864	335	225
31.75	1 1/4	6	157	940	536	360
34.93	1 3/8	7	160	1,118	536	360
38.10	1 1/2	7	174	1,219	536	360
41.27	1 5/8	7	185	1,295	640	430
44.45	1 3/4	7	192	1,346	878	590
50.80	2	8	225	1,803	1,116	750
57.15	2 1/4	8	232	1,854	1,116	750
63.50	2 1/2	9	237	2,134	1,116	750
69.85	2 3/4	10	254	2,540	1,116	750
76.20	3	10	269	2,692	1,786	1,200