


CATEGORY 5E UTP CABLE DIRECT BURIAL GEL FILLED

PSC-CAT5EXT-GEL



Application

- Voice, Data, Security and Video Applications. IP Megapixel CCTV/Analog Installations
- Wire Access Points
- Gigabit Indoor Video/data installations
- Long distance PoE feeding
- Generic cabling systems. Outdoor installations. Filled with compound to prevent water penetration

Standards

- ANSI EIA/TIA 568 C.2;
- ISO/IEC 11801 2nd Edition;
- EN 50173;
- IEEE 802.3at

Construction

Conductor	Bare copper wire (AWG24/0.45±0.005mm)
Insulation	Polyethylene, Ø 0.85±0.02 mm
Twisting	2 cores to the pair
Cable lay up	4 pairs to the core
Filling	Jelly Compound to prevent moisture migration.
Rip Cord	Yes
Outer Sheath	Black LDPE UV Resistant
Diameter	5.30 ± 0.2 mm

Mechanical properties

Minimum bending radius	Installation	8 x D
	Installed	4 x D
Temperature range	during operation	-40°C ~ + 60°C
	during installation	-20°C ~ + 50°C

Electrical properties @ 20°C

Electrical properties @ 20°C	
Dielectric strength	2.5 KV dc-2 seconds
Conductor resistance	Max 11 .00 ohm/100M at 20°C
Max. Ring resistance	16.8 Ohm/100M at 20°C
Max. Mutual capacitance	560 pf/100M
Max. Capacity unbalance	330 pf/100M
Mean characteristic impedance 100 MHz	100 ± 15 Ω
Nominal velocity of propagation	approx. 67 %
Propagation delay	Nominal 535 ns/100m
Delay skew	Nominal 20 ns/100m
Test voltage (DC, 1 min)	1000 V
Core/Core Coupling attenuation	≥ 40 dB

Nominal transmission characteristics @ 20°C

Fre.	Attenuation	NEXT	PS-NEXT	ACR	PS-ACR	ACRF	PS- ACRF	Return loss
(MHz)	dB/100m)	(dB)	(dB)	dB/100m)	dB/100m)	dB/100m)	dB/100m)	(dB)
1	1,9	71	68	69,1	66,1	68	65	20
4	3,7	62	59	58,3	55,3	56	53	23
10	6	56	53	50	47,0	48	45	25
16	7,6	53	50	45,4	42,4	44	41	25
20	8,5	51	48	42,5	39,5	42	39	25
31,2	10,7	49	46	38,3	35,3	38	35	24
62,5	15,7	44	41	28,3	25,3	32	29	22
100	19,8	41	38	21,2	18,2	28	25	20

© SYSCOM, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Syscom: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Syscom. The information is believed to be correct at the time of issue. Syscom reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Syscom.