





Part. 01

Background

Part. 02

**Solution Introduction** 

Part.03

**Display Template** / Product Showcase

Part.04


Part. 01 Background

### // Background





In the special time, store owners hope to control the number of people in the store to a certain range and show the numbers to consumers in an friendly way.



On the other hand, consumers hope to have their own temperature information in real time to conduct self-check and avoid places where people are too dense.

Part. 02 Solution Introduction



### / What can we do?





### People Counting

Displays the number of people have entered and people who can still enter. Alerts if it exceeds the maximum number of people.

#### Mask Detection

When a customer without a mask is detected, a customized text prompt will pop up.

### **Temperature Screening**

Displays the image of thermal camera and temperature detection results.

### □ Advertising

Play advertising pictures or videos in a loop.



Supermarket



Restaurant



Shop

Hotel

# **// Solution Topology**






FocSign Information Release System

Support three types of digital signage

Streams can be taken directly from the camera via the network or through NVR

With a variety of cameras to achieve density control, mask detection and etc.



### **Multiple Entrances**





- Support the unified management of multiple entrances and the display the unified data of multiple people counting cameras.
- Can directly display the thermal image or optical image of the thermal imaging camera of each entrance.
- According to the position of the digital signage, different advertising pictures or videos can be displayed.

Part. 03
Display
Template





If it is detected that someone is not wearing a mask, it will prompt "Please wear a mask!"



Shows the total number of people in the store and the number of people who can still enter. If the total number of people exceeds the limit, the color will change to red and prompt a text "Please wait!" This part can display the optical image or thermal image of the thermal camera, and can display the body temperature in real time.

A total of 8 templates for choice. Density control, mask detection, temperature screening and advertising functions can be combined flexibly.





















### 1. Flow Control







#### 2. Flow Control + Mask Detection








- 3. Flow Control + Mast Detection
- + Temperature Screening






Step 3: Release the

program to terminals



Step 1: Choose a template

#### FocSign Lite



Step 2: Add materials: NVR (Optional), IPC, pictures or videos

Part. 04
Product
Showcase



### // Product Showcase









Floor-standing Digital Signage

DS-D6055FL-B/S DS-D6043FL-B/S

Wall-mounted Digital Signage

DS-D6022FL-B DS-D6032FL-B DS-D6043FN-B **Monitor** 

DS-D5022QE-B DS-D5032QE

**Digital Signage Box** 

DS-D60C-B



**Thermal Camera Bracket** 

BRT-55 inch bracket-TY
Support thermal camera DS-2TD1217B-3/PA

### / How to



Step 1: Read the how to

Microsoft Word ÎÄμμ

Step 2: Download and install the FocSign software

https://one.hikvision.com/#/link/mPt7a3iFqKhYknH36nfb
Password : Cdeq

Step 3: Download and update the OTA of terminals

FTP: /00 Oversea Products/06 Transmission\_Display/02 Commerical Display/02 Digital Signage/04 Firmware/Digital Signage/Digital Signage 3.0.0/二代/

### **Afterwards**



#### Digital signage can be used for daily advertising.





