



SEC-412

SnapSeal™ Entry Cushion with 4 holes for 1/2 in corrugated coaxial cable

Dimensions

| | |
|--------------|---------------------|
| Nominal Size | 1/2 in |
| Height | 101.60 mm 4.00 in |
| Length | 31.75 mm 1.25 in |

General Specifications

| | |
|--------------------|--|
| Cable Type | Corrugated |
| Cables per Cushion | 4 |
| Color | Black |
| Includes | Compression ring SnapSeal™ entry cushion |
| Material Type | Thermoplastic elastomer (TPE) |
| Ordering Note | CommScope® non-standard product |
| Package Quantity | 1 |

Mechanical Specifications

| | |
|--|--|
| UV Resistance Test Method | MIL-STD-810E, Procedure 11, Method 505 |
| UV Resistance, minimum with no degradation | =1000 hours |
| Weather Resistance Test Method | 04AS00-03.9.0 IEC 60529:2001, IP66 |

Packed Dimensions

| | |
|-----------------|-------------------|
| Height | 169.9 mm 6.7 in |
| Length | 99.8 mm 3.9 in |
| Shipping Weight | 0.80 kg 1.76 lb |
| Width | 129.8 mm 5.1 in |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |