

# Little Giant® Ladder Systems

# SENTINEL™

COMBINATION LADDER | TYPE IA + IAA | OSHA + ANSI COMPLIANT

## 10' & 12' 2-IN-1 LADDER STEPLADDER + LEANING

### 1. ROTATING WALL PAD

The rotating wall pad allows you to safely work on inside corners, outside corners, walls and studs. With its non-marring surface, you can lean your ladder to get closer to your work without fear of damaging the surfaces.

### 2. EXTRA-WIDE COMFORT STEPS

At 3.12" wide, the rungs on the Sentinel are already comfortable, but the top two steps are a massive 6.25" for maximum comfort while working.

### 3. NON-CONDUCTIVE, HI-VIZ GREEN FIBERGLASS

Our Hi-Viz green fiberglass is lightweight and non-conductive. The vibrant green color is proven to increase visibility, preventing injuries from people or objects bumping the ladder while in use.

### 4. GROUND CUE®

Up to 20% of all ladder injuries happen from missing the bottom step while descending the ladder. Ground Cue makes an audible and tactile "click" that alerts you when you've reached the bottom step of the ladder.

### 5. RAIL LOCKS®

Locks your ladder closed for easy transport and safe use in the leaning ladder position.



 NON-CONDUCTIVE FIBERGLASS  
FIBRA DE VIDRIO NO CONDUCTORA





Extra-Wide Comfort Steps



Rotating Wall Pad



Leans Against Walls



Leans on Outside Corners



Ground Cue®



Leans on Inside Corners

## PRODUCT DESCRIPTION

Sometimes, you need to get closer to the task at hand than a standard A-frame offers, and that's where the Sentinel comes in. The Little Giant® Sentinel combines two ladders in one, A-frame and leaning ladder, making it a versatile tool to help you get stuff done. The Sentinel is available as a Type IA and Type IAA, rated to hold 300 or 375 lbs. This ladder meets or exceeds all OSHA and ANSI standards. Type IAA features 2 comfort steps and Ground Cue. Type IA has 1 comfort step and no Ground Cue.

## 1-YEAR LIMITED WARRANTY

Part #	Model	Ladder Size	Step ladder Highest Standing Level	Step ladder Max Reach*	Leaning Highest Standing Level	Leaning Max Reach*	Storage Depth	Weight
15920-002	M10 IA	10'	7' 8"	14' 2"	6' 8"	13' 2"	7"	38 lbs
15922-002	M12 IA	12'	9' 7"	16' 1"	8' 7"	15' 1"	7"	46 lbs
15910-002	M10 IAA	10'	7' 8"	14' 2"	6' 8"	13' 2"	7"	40 lbs
15912-002	M12 IAA	12'	9' 7"	16' 1"	8' 7"	15' 1"	7"	48 lbs

\*A 1.67 m person with a .3 m vertical reach