HIKVISION

HIKVISION HS-UDIMM-U10 DDR

HIKVISION HS-UDIMM-U10 is a DDR4 DRAM, It adpoted original nand flash based on HIKVISION's mature production processes, by which strong compatibility, high operation stability and better costeffectiveness are guaranteed. It could be widely applied in PC assembly, high-speed broadband and high-end system.



Avaliable Model:

| Model | Description | |
|---|------------------------------|--|
| HS-UDIMM-U10 8GB /HKED4081CAA2F0ZB2 | Frequency 3200MHz,CL16,1.35V | |
| HS-UDIMM-U10 16GB/HKED4161DAA2F0ZB2 | Frequency 3200MHz,CL16,1.35V | |
| HS-UDIMM-U10 16GB*2/HKED4161DAA2F0ZB2*2 | Frequency 3200MHz,CL16,1.35V | |

Feature:

Cost-Effectiveness

Original NAND Flash, which helps to improve system stability and operation performance

• Strong Compatibility

Based on HIKVISION data processing optimization to guarantee better compatibility, which could be compatible with mainstream motherboard





Specification:

| Name | HIKVISION DDR4 U10 | | |
|-------------|--------------------|-------------------|---------------------|
| Model | HS-UDIMM-U10 | HS-UDIMM-U10 | HS-UDIMM-U10 |
| | HKED4081CAA2F0ZB2 | HKED4161DAA2F0ZB2 | HKED4161DAA2F0ZB2*2 |
| Capacity | 8G | 16G | 16G*2 |
| DDR Gen. | DDR4 | | |
| Frequency | 3200MHz | | |
| Pin | 288pin | | |
| Latency | CL16 | | |
| Voltage | XMP 1.35V | | |
| Size(mm) | 133.35×31.25×3.90 | | |
| Temperature | 0~85 ℃ | | |
| Warranty | Lifetime | | |

Note:

- Parameters in this specifications are usually the maxium values of this product series, different capacity might have certain deviation, take the actual performance as final reference
- Test are conducted under specific system, hardwares, softwares, operation system and functions, any changes on them might result different test result.

Distributed by

Г

Γ

L



Headquarters Room 307, Unit B, Building 2, 399 Danfeng Road, Binjiang District, Hangzhou, Zhejiang, China