


## Desire(S) series



### Introduction

Relying on the security background of Hikvision, we are committed to developing the four major businesses of solid state drives, memory cards, private network disks, and mobile storage, with a sound supply chain system and perfect after-sales process. On the technology side, Desire(S) series adopts the advanced SSD controller and 3D NAND Flash, and coordinates with HIKVISION’s self-designed NAND Flash management firmware to ensure the read/write speed and data safety.

On the production side, Desire(S) series adopts the good quality 3D NAND Flash and BGA , and is manufactured by the automatic production line. It has been tested according to the standard of video surveillance server, so that it offers better stability.

### Features

- High R/W Speed SATA interface

Max. read speed up to 560 MB/s

- 3D NAND Technology

3D NAND technology helps to develop higher capacity, performance, and stability

- Anti-shock and anti-fall

No mechanical structure, using electronic chip control, data more secure.

- Application Field

Applicable to personal computers, laptops, PS4, etc.

### Ordering Information

Capacity	Model
Desire(S) 512G	HS-SSD-Desire(S)
Desire(S) 1024G	HS-SSD-Desire(S)

#### Note

Please contact the local sales for detailed model information.

## Specification

Model	Desire(S) series	
Capacity	512GB	1024GB
Form Factor	2.5 inch	
Max. Seq. Read	560 MB/s	560 MB/s
Max. Seq. Write	505 MB/s	520MB/s
Max. Ran 4 K Read (IOPS)	45 K	75 K
Max. Ran 4 K Write (IOPS)	75 K	75 K
Max. Power Consumption	1.4W	1.9W
TBW	84TB	176TB
MTBF	1,500,000 hours	
Storage Medium	3D QLC	
Interface	SATAIII	
Working Temperature	0 °C to 70 °C (32 °F to 158 °F)	
Storage Temperature	-40 °C to 85 °C (-40 °F to +185 °F)	
TRIM	Supports	
Warranty	3 years	
Weight	≤34.4g	

### Note

1. Specifications are subject to change without notice.
2. 1 MB=1,000,000Bytes, 1 GB=1,000,000,000Bytes, Unformatted Capacity. User accessible capacity may vary depending on operating environment and formatting.
3. Operating Temperature (0 °C ~70 °C) is subject to SSD's S.M.A.R.T. display.

## Revision History

Version	Description	Date
V1.0.0	Desire(S) series	20211115

Data subject to change without notice.

© 2021 HANGZHOU HIKSTORAGE TECHNOLOGY CO.,LTD. All rights reserved.

Unless otherwise expressly stated herein, HIKSTORAGE does not make any warranties, guarantees or representations, express or implied, regarding to the Manual, any information contained herein.

The Manual includes instructions for using and managing the Product. Pictures, charts, images and all other information hereinafter are for description and explanation only. The information contained in the Manual is subject to change, without notice, due to firmware updates or other reasons. Please find the latest version of this Manual at the HIKSTORAGE website ([www.hikstorage.com](http://www.hikstorage.com)).