CDP UPO11-1RTAX 1000VA/1000W PF 1.0 Online UPS 2U 19' RT, LCD UL, FCC, CE 120 Vac

Brand : CDP

Product code: UPO11-1RTAX

Product name : UPO11-1RTAX 1000VA/1000W PF 1.0 Online UPS 2U 19' RT, LCD UL, FCC, CE 120 Vac

UPO11-1RTAX 1000VA/1000W PF 1.0 Online UPS 2U 19' RT, LCD UL, FCC, CE 120 Vac

CDP UPO11-1RTAX 1000VA/1000W PF 1.0 Online UPS 2U 19' RT, LCD UL, FCC, CE 120 Vac:

UPO11-1RTAX
Chicago Digital Power Enterprise 1000VA double conversion online ups in a R/T configuration for 19-inch rack installation or Floor mount. Incorporated power full batteries and wide input voltage range of 55Vca - 150Vca ±3% and selectable output voltage of 100-110-115-120-125Vac precise output. with auto diagnostics and advance LCD displays that provide operational information as well as communication for remote monitoring and control.

Advanced high frequency transformer reproduces perfect AC while eliminating Spikes/surges, line noise and voltage fluctuations, Compact reliable design that includes certifications from international regulatory agencies like NOM, ISO9001-2015, ISO14001, RETIE, TÜV, UL.

* Product also available in 220V labeled with (i).

Features	
UPS topology *	Double-conversion (Online)
Output power capacity *	1 kVA
Output power *	1000 W
Waveform *	Pure sine
Input operation voltage (min) *	55 V
Input operation voltage (max) *	150 V
Input frequency *	50/60 Hz
Output operation voltage (min)	100 V
Output operation voltage (max)	127 V
Output frequency	50/60 Hz
Surge energy rating	844 J
Number of input phases	1
Number of output phases	1
Efficiency (On-line mode)	90%
Efficiency (ECO mode)	97%
Input power factor	0.99
Output power factor	1
Crest factor	3:1
Emergency Power Off (EPO)	✔
Output voltage Total Harmonic Distortion (THD)	4%
Input current Total Harmonic Distortion (THD)	3%
EMI/RFI noise filtering	✔
Noise level	50 dB
Surge protection	✔
Power protection features	Overload, Short circuit
Audible alarm(s)	✔

Ports & interfaces	
AC outlet types	NEMA 5-15R
Power plug	NEMA 5-15P
AC outlets quantity	8 AC outlet(s)
USB port	✔

Battery	
Number of batteries supported	2
Typical backup time at full load	7 min
Typical backup time at half load	15 min
Battery recharge time	4 h
Cold start	✔

Design	
Form factor *	Rackmount
Housing material	Metal
Rack capacity	2U
Cable length	1.5 m
Cooling type	Active
Built-in fan	✔
Product colour *	Black
Display type	LCD
LED indicators	✔
International Protection (IP) code	IP20

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m

Certificates	
Certification	NOM, ISO9001-2015, ISO14001, RETIE, TÜV, UL

Weight & dimensions	
Width	500 mm
Depth	560 mm
Height	180 mm
Weight	16.8 kg

Packaging data	
Package weight	16.3 kg

Ports & interfaces	
USB 2.0 ports quantity	1
RS-232 ports	1
Emergency Power Off (EPO) connector	✔

Battery	
Battery technology	Lead-Acid
Battery capacity	7 Ah
Battery voltage	12 V

Logistics data	
Pallet gross length	120 cm
Pallet gross width	100 cm
Pallet gross height	2.17 m
Pallet gross weight	652 kg
Master (outer) case net weight	16.8 kg
Master (outer) case gross weight	16.3 kg
Products per master (outer) case	1 pc(s)

0879071000598

879071000598

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 09-OCT-2026. Prints or copies of Information are only valid on the printed Publication date