HIKVISION



Panic Button User Manual

COPYRIGHT ©2018 Hangzhou Hikvision Digital Technology Co., Ltd. ALL RIGHTS RESERVED.

Any and all information, including, among others, wordings, pictures, graphs are the properties of Hangzhou Hikvision Digital Technology Co., Ltd. or its subsidiaries (hereinafter referred to be "Hikvision"). This user manual (hereinafter referred to be "the Manual") cannot be reproduced, changed, translated, or distributed, partially or wholly, by any means, without the prior written permission of Hikvision, Unless otherwise stipulated, Hikvision does not make any warranties, guarantees or representations, express or implied, regarding to the Manual.

About this Manual

The Manual includes instructions for using and managing the product, Pictures, charts. images and all other information hereinafter are for description and explanation only. The information contained in the Manual is subject to change, without notice, due to firmware updates or other reasons. Please find the latest version in the company website (http://overseas.hikvision.com/en/).

Please use this user manual under the guidance of professionals.

HIKVISION Trademarks Acknowledgement and other Hikvision's trademarks and logos are the properties of Hikvision in various jurisdictions. Other trademarks and logos mentioned below are the properties of their respective owners. Legal Disclaimer

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THE PRODUCT DESCRIBED, WITH ITS HARDWARE, SOFTWARE AND FIRMWARE, IS PROVIDED "AS IS". WITH ALL FAULTS AND ERRORS, AND HIKVISION MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY, SATISFACTORY QUALITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF THIRD PARTY, IN NO EVENT WILL HIKVISION, ITS DIRECTORS, OFFICERS, EMPLOYEES, OR AGENTS BE LIABLE TO YOU FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES, INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, OR LOSS OF DATA OR

DOCUMENTATION. IN CONNECTION WITH THE USE OF THIS PRODUCT, EVEN IF HIKVISION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

REGARDING TO THE PRODUCT WITH INTERNET ACCESS, THE USE OF PRODUCT SHALL BE WHOLLY AT YOUR OWN RISKS. HIKVISION SHALL NOT TAKE ANY RESPONSIBILITES FOR ABNORMAL OPERATION, PRIVACY LEAKAGE OR OTHER DAMAGES RESULTING FROM CYBER ATTACK, HACKER ATTACK. VIRUS INSPECTION, OR OTHER INTERNET SECURITY RISKS: HOWEVER, HIKVISION WILL PROVIDE TIMELY TECHNICAL SUPPORT IF REQUIRED.

SURVEILLANCE LAWS VARY BY JURISDICTION. PLEASE CHECK ALL RELEVANT LAWS IN YOUR JURISDICTION. BEFORE USING THIS PRODUCT IN ORDER TO ENSURE THAT YOUR USE CONFORMS THE APPLICABLE LAW. HIKVISION SHALL NOT BE LIABLE IN THE EVENT THAT THIS PRODUCT IS USED WITH ILLEGITIMATE PURPOSES

IN THE EVENT OF ANY CONFLICTS RETWEEN THIS MANUAL AND THE APPLICABLE LAW. THE LATER PREVAILS.

> EN 50130-4:2011+A1:2014: EN61000-6-3:2007+A1:2011



This product and - if applicable - the supplied accessories too are marked with "CE" and comply therefore with the applicable harmonized European standards listed under the EMC Directive 2014/30/EU, the LVD Directive 2014/35/EU. the RoHS Directive 2011/65/EU.

Spécification

Matériau du boîtier

Dimensions (L x I x H)

Tension de fonctionnement ≤ 250

Courant de fonctionnement ≤ 300 Méthode de câblage

Bouton de panique

ABS

Normal ouvert/Normal fermé

53.5 mm * 49.5 mm * 32.5 mm

ΕN

Appearance

Specification

Front View	(4)
	<u> </u>

0 0	_	О
09		-
	•	ı
II 4		r.
- 0		느
	ערוש א	ГΨ
¢.		
		_
l e	177	0

Side View

Rear View



Panic Button	
Shell Material	ABS
Operation Voltage	≤250
Operation Current	≤300
Wiring Method	NO/NC
Dimension(LxWxH)	53.5mm*49.5mm*32.5mm

FR

Apparence

Vue de face

|--|--|

1			

Vue arrière



Vue latérale



Apresentação

Visão frontal (#)

Especificações

Bot	ão de pânico
Material do invólucro	ABS
Tensão de operação	≤250
Corrente de operação	≤300
Método de fiação	NA/NF
Dimensões (C x L x A)	53,5 x 49,5 x 32,5 mm

Visão traseira



Visão lateral



ES

Apariencia

Vista frontal



Vista trasera



Vista lateral



Especificación

Botón de emergencia	
Material de la carcasa	ABS
Tensión de funcionamiento	≤250
Corriente de funcionamiento	≤300
Método de cableado	NA/NC
Dimensiones (L. x An. x Al.)	53,5 mm x 49,5 mm x 32,5 mm

IΤ

Aspetto



Specifiche

Pulsante Panico	
Materiale del guscio ABS	
Tensione di funzionamento	≤ 250
Corrente di funzionamento	≤ 300
Metodo di cablaggio	NA/NC
Dimensioni (L x P x A)	53,5 mm x 49,5 mm x 32,5 mm

Vista posteriore



Visuale laterale



RU

Внешний вид





Вид сзади



Вид сбоку



Технические данные

Аварийная кнопка	
Материал корпуса	АБС
Рабочее напряжение	≤ 250
Рабочий ток	≤ 300
Способ подключения	НОРМАЛЬНО РАЗОМКНУТЫЕ/ НОРМАЛЬНО ЗАМКНУТЫЕ
Размеры (Д х Ш х В)	53,5 x 49,5 x 32,5 mm