
XMRC37



Advantages

- Embedded AI technologies improve law enforcement efficiency
- Dual camera lens design support wider angle and longer distance video recording
- Rotating lens enable officer quickly select key areas for monitoring
- Compact appearance
- Easy to install with 3M tape
- 1080P high-definition resolution ensures crystal clear records of law enforcement process

Specifications

Product Model		
	Vigilant Dual Camera	
Sensor Parameters		
	Image Sensor	1/2.8" CMOS
	Shutter Speed	Automatic Shutter: 1/30s-1/5000s Manual Shutter: 1/30s-1/100000s
	Effective Pixels	1920 (H) *1080 (V)
	S/N	≥48dB
	Minimum illumination	0.05lux/F1.2
Resolution		
	Selective Resolution	1080P/720P
Lens		
	Wide-angle Lens	2.6mm
	FOV (2.6mm wide-angle lens)	130 degrees
	Telephoto Lens	8mm
	FOV (8mm telephoto lens)	46 degrees
	Rotation Angle	±25 degrees
Audio & Video Compression Format		
	Video Compression Format	H.265/H.264
	Audio Compression Format	G.711A/G.711U/ADPCM/G.726
Video Parameters Control		
	Wide Dynamic Range	Support

	(WDR)	
	Gain Control	Automatic/Manual
	White Balance	Automatic
	Backlight Compensation	Support
Audio Input		
	Built-in Mic	Support
Overview		
	Dimension	3.90 (L) * 1.57(W) * 3.23(H) inch
	Weight	273.1 g
	Operation Temperature Range	-40.0°F-158°F(-40°C-70°C)
	Storage Temperature Range	-40.0°F-185°F (-40°C-85°C)
	Operating Humidity	95% non-condensing

Product Dimensions (Unit: mm)

