HIKVISION

DS-PD2-T12P-WEL

Wireless Outdoor Dual-Tech Detector

DS-PD2-T12P-WEL delivers long range signaling, multi-award-winning two-way wireless technology, heightened false alarm immunity with Dual-Vision Pet Immune detection technology, as well as a host of features that make this a steadfast detector that's quick and easy to install. Offering 90° detection (install between 1.2m), the brandnew DS-PD2-T12P-WEL can provide a maximum detection range of 12m.



AVAILABLE MODEL

| DS-PD2-T12P-WEL | Wireless Outdoor Dual-Tech Detector |
|-------------------------|---|
| DS-PDB-EX-Wall bracket | Wall bracket (Need to order separately) |
| DS-PDB-EX-Adapter | Detector Bracket for Extending coverage angle to 90 degrees (Need to |
| | order separately, using together with DS-PDB-EX-Wall bracket) |
| DS-PDB-EX-Fixed bracket | Fix two external detectors to give added coverage to perimeters (Need |
| | to order separately) |

*All bracket need to order separately.

MAIN FEATURES

- Microwave + 2 independent PIR
- Detection Range : 12m with Volumetric coverage 90°
- Alarm: Tamper Alarm, Intruder Alarm
- Adjustable PIR/MW range
- Dual-Vision Pet Immune (up to 35kg)
- Anti-Sway Analytics
- Blue Wave Technology
- IP55 Heavy Duty Design

SPECIFICATION

| Wireless Outdoor Dual-Tech Detector | | |
|-------------------------------------|-------------------------------------|--|
| Detection Range | 12m, detection angle: 90° | |
| Detection Speed | 0.25m/s ~ 3m/s | |
| Transmission Range | 800m in open space | |
| Animal Immunity | Up to 35kg | |
| Power Supply | 2×3V 4700mAH Lithium Battery packs, | |
| | up to 3 years Battery life | |
| Transmission frequency | 433MHz | |
| Operation Temperature | -30°C ~ +70°C | |
| Dimension(L*W*H) | 188mm*77mm*84mm | |
| Weight | 300g (without bracket) | |
| Installation Environment | Outdoor | |
| Installation Height | 1.2m | |