blueparrott GN

BlueParrott M300-XT

ENGINEERED TO KEEP YOU CONNECTED ON THE GO.

Our smallest and lightest Bluetooth® headset with 80% noise cancellation.

- > 80% noise cancellation with 2-mic tech
- > Just 0.7 oz / 20 g for all day comfort
- IP54-rated protection against dust and moisture
- > Up to 14 hours of talk time
- > Up to 300 ft / 100 m wireless range
- > Customizable BlueParrott Button™



TECHNICAL SPECIFICATIONS			
Noise reduction on calls	Yes		
Speaker size	10.3mm 0.41in		
Speaker max input power	5 mW		
Speaker frequency range	20Hz - 20kHz		
Speaker impedance	32 Ω		
Audio codecs supported	SBC		
Microphone type	2 x MEMS		
Microphone sensitivity	-42±1dB (0dB=1V/Pa, at 1KHz)		
Certifications and compliance	FCC, ISED, CE, RoHS, REACH, Proposition 65		
Headset form factor	BT Mono		
EarGels	Large, medium, small		
Connectivity	Bluetooth®		
Bluetooth profiles	A2DP v1.3, AVRCP v1.6, HFP v1.7, HSP v1.2		
Bluetooth version	5.1		
Operating range	Up to 100m 300ft		
Bluetooth pairing list	Up to 8 devices		
Simultaneous Bluetooth connections	2		
NFC	Yes		
Talk time	Up to 14 hours		
Corded charging (cable dependent)	USB-C		
Charging time	Up to 150 minutes		
Standby time	Up to 420 hours		
Standby time Battery type	Up to 420 hours Rechargeable lithium ion battery		
	Noise reduction on calls Speaker size Speaker max input power Speaker frequency range Speaker impedance Audio codecs supported Microphone type Microphone sensitivity Certifications and compliance Headset form factor EarGels Connectivity Bluetooth profiles Bluetooth version Operating range Bluetooth pairing list Simultaneous Bluetooth connections NFC Talk time Corded charging (cable dependent)		

General info	Box content	EarGels, headset, user documents, USB cable
Generaliiio		, , , , , , , , , , , , , , , , , , , ,
	Packaging dimensions (WxHxD)	41.5mm x 175mm x 131mm 1.63in x 6.89in x 5.16ir
	Main unit dimensions (WxHxD)	110.7mm x 61mm x 25.4mm 4.36in x 2.4in x 1in
	Weight	20g 0.7oz
	USB cable length	1.2m 3.9ft
	IP rating	IP54
	Warranty	1 Year
Extended info	Operating temperature	-10°C to 60°C 14°F to 140°F
	Storage temperature	-10°C to 45°C 14°F to 113°F

PRODUCT TYPE	SKU	DESCRIPTION
Products	204347	BlueParrott M300-XT
Accessories	204354	BlueParrott M300-XT Refresher Kit